



SECURITY



26

Enhance the safety of your premises with our advanced Security solutions. Our comprehensive range includes surveillance cameras, access control systems, and alarm systems, all designed to provide robust protection and peace of mind. Whether for residential, commercial, or industrial use, our security products are engineered to deter threats and ensure the safety of your property and personnel.



SMART WIFI DIY ALARM SYSTEMS

- 128 Bit Code- Hopping technology ensures a secure and robust connection to the control hub
- Various Connectivity Options include: WI-Fi and GSM

ACDC SMART SWITCH Wi-Fi



MAXKIN ONTIPS PRO GSM / Wi-Fi



Mobile phone not included



Smartcam Alarm System

Code	Description	App
MXK-N8-WIFI/2G	DIY Hybrid WiFi / GSM Smartcam Alarm System	Ontips Pro

Kit Includes

- 1 x Smart hub with built-in camera and motion detection (PIR)
- 1 x Door contact, with built in vibration sensor
- 1 x Remote

Features

- Accommodates up to 50 add-on devices
- Night Vision
- 16hrs Battery Backup (internal lithium battery)
- Monitors temp and humidity
- SMS Alerts
- GSM - Communication back-up if WiFi fails. Sim Card required (not supplied)



Wireless Alarm System

Code	Description	App
MXK-X1-2G-PLUS-T	DIY GSM/Wi-Fi Wireless Alarm System	ACDC Smart
MXK-X1-2G-PLUS	DIY GSM Wireless Alarm System	Ontips Pro

Kit Includes

- 1 x Smart Hub
- 2 x Remotes
- 1 x Door Contact
- 1 x PIR (Motion Sensor)

Features

- Accommodates up to 50 add-on devices
- SMS Alerts for low battery
- Stores up to 5 telephone numbers
- 16hrs Battery Backup (internal lithium battery)
- Dual-colour LED status indicator

When the alarm system is triggered the system immediately rings the nominated telephone number and sends a message. The system also sends a system status message for power failures, restoration of power and low battery. The zone names can be customized so that alarm locations are easily recognised.



Portable Wi-Fi Alarm System

Code	Description	App
MXK-CONCH-T	DIY Two-Way Portable Wi-Fi Alarm System	ACDC Smart
MXK-CONCH	DIY Two-Way Portable GSM Alarm System	Ontips Pro

Kit Includes

- 1 x Smart Hub
- 1 x Remote
- 1 x Door contact with built-in motion sensor

Features

- 100m coverage area with 2hrs battery backup
- Accommodate up to 40 devices
- Built in siren
- Tri-colour LED status indicator
- Multi-function button for network/device enroll



Portable Wireless Alarm System

Code	Description
MXK-TUTTI	DIY Two Way Portable Wireless Alarm System

Kit Includes

- 1 x Smart Hub
- 1 x Remote
- 1 x Door contact

Features

- System can accommodate up to 40 devices
- Touch screen keypad on device
- Built in siren
- 12 Hours back up battery



Sleek modern design with user friendly features. The voice prompts quickly inform which zones have been triggered. Integrated management of the alarm system with wireless touchscreen provides protection and peace of mind for home owners. The LED backlight provides instant indication of system status.

SMART WIFI DIY ALARM SYSTEMS

Mobile phone not included



Screenshot



Code	Description	App
MXK-IP-100	720p indoor Wi-Fi Camera with Motion Sensor	Ontips Pro


Features

- Resolution 1280x720p
- Video recording
- Ontips Pro APP
- Two way communication
- Day / Night Vision
- Real time notifications
- Range 7-10m x 120°
- 2 way speech
- 8-32GB MicroSD (excl)

SMART WIFI DIY ALARM SYSTEM - ACCESSORIES


	Magnet Sensors				4 Button Remote	Keypad
FHSS Technology Range: Up to 80m line of sight	2-in 1 Batteries Incl. 	2-in 1 Batteries Incl. 	Battery Incl. 	Battery Incl. 	Battery Incl. 	3-in-1 Batteries Incl. 2 x RFID Tags 
Code	MXK-SS-P01	MXK-SS-V01	MXK-DWS-300	MXK-DWS-302	MXK-RC-101	MXK-KP-A1
Description	Door/Window Contact & PIR Motion Sensor. Detection: 110°/8m	Door/Window Contact & Vibration Sensor	Door/Window Sensor	Roller Shutter Door Sensor	Multi-function Keyfob Remote Control	Wireless Keypad
Spare Battery	E96BP2	E96BP2	98215	98215	CR2032/5	98111
	Water Leak Detector	PIR Motion Sensors			Smoke Detector	Gas Detector/Siren
FHSS Technology Range: Up to 80m line of sight	Battery Incl. 	Indoor Batteries incl. 	Indoor Adaptor incl. 	Outdoor Adaptor Incl. 	Battery Incl. 	Plug-in 
Code	MXK-SS-F01	MXK-PIR-600	MXK-PIR-603	MXK-PIR-602	MXK-SD-200	MXK-SP-G01
Description	Wireless Leak Detector	PIR Motion Sensor	M/Wave & PIR Sensor, Pet Immune (≤ 20kg)	M/Wave & PIR Intelligent Sensor Pet Immune (≤ 20kg)	Smoke Detector Low battery alarm	Natural Gas Detector 90dB Sounder
Sensor Range	95cm Cable	8m x 110°	12m x 110°	12m x 110°	Monitors 60m²	10% LEL
Spare Battery	E96BP2	98208	—	—	98215	—
	Beam Detection - IP66			Outdoor Sirens - IP56	Repeater/Siren	
FHSS Technology Range: Up to 80m line of sight	Adapter Included 	Adapter Included 	Solar Powered 	Built-in strobe light 12VDC + Battery 	Plug-in + Battery  Disarmed Armed Alarm	
Code	MXK-IB-400-*	MXK-IB-410	MXK-IB-420	MXK-WS-901	MXK-SP-R01	
	Dual-Beam Infrared Sensors	Quad-Beam Infrared Sensor	Solar Power Multi Beam Sensor	115db Siren With Battery Backup	Increases wireless range up to 300m	
	*30M (30m), 60M (60m)	20m max	10m max	—	90dB Sounder	

SMART ZIGBEE SECURITY DEVICES



Smart Gateway Home

App Home



Smart Gateway - A low power-consuming Zigbee module that allows ACDC SMART App to add different Zigbee devices.

Code	Description
CP-GWF01	Zigbee Smart Gateway

Package Includes:

- Zigbee smart gateway
- DC5V USB power supply
- Network cable
- Network connection via LAN/WIFI

Accessories

	Door/Window Sensor	Temperature & Humidity Sensor	PIR Sensor	Smoke Detector	Water Leak Detector
Code	CP-ZDC01	CP-ZTH02	CP-ZMD01	CP-ZSD01	CP-ZWL01
Description	Zigbee Door/Window Sensor	Zigbee Temperature and Humidity Sensor	Zigbee PIR Sensor	Zigbee Smoke Detector	Zigbee Water Leak Detector
Supply Voltage	3.0V - CR2032	3.0V - CR2032	3.0V - CR2450	12VDC External adaptor	3.0V - CR2032 Battery

SMART WIFI GARAGE DOOR CONTROLLER

Smart Wifi Garage Door Controller - One Controller per Garage Door

Integrate to your Wi-Fi System and you can control and monitor your garage door using your Smart Phone

Code	Input Voltage	Max Load	Output Contact	Size (mm)
AS-MS-102	100-240VAC	16A	NO	87 x 40 x 23



WiFi Control



App Control



Open / Close Remotely




Alarm Notification



Count Down Timer





Switching Schedules




Features

- Keeps records of all door Open/Close events
- Real time door position status


Wiring Diagram




Door position



Events Records



Set Countdown Times



Set Alarm

WIRELESS ALARM/CHIME SYSTEM

	PIR Motion Sensor	DC Alarm/Chime Warning Device	AC Power Receiver
	Indoor IP21 		Max. loading: 10A 
Code	AEC-3004RZD	RC02DC	RC03
Description	- RF Transmitting $\pm 60\text{m}$ - Plastic construction - Sensor range: $8\text{m} \times 360^\circ$ - Control receivers up to 60m away 256 sets of changeable system code is available - Standard voltage: 1pc 9V battery (excl) - Able to control RC02DC, RC03	- RF Transmitting $\pm 60\text{m}$ - Plastic construction (Indoor) - Power: Adapter 6V 300mA or A 1.5V 4 pcs or AA 1.2V 4pcs (adapter & batteries not incl.) - With chime/off/alarm switch - Volume adjustment: 90dB maximum - Time adjustment: 5secs to 2mins - Receiving distance of 60m from transmitter 256 sets of changeable system code	- Outdoor/Indoor RF Receiving $\pm 60\text{m}$ - Plastic construction (Indoor) - Power source: 240VAC 50Hz - Function: transmitter controls ON/OFF function - Time adjustment: 5secs to 7mins - Control receivers up to 60m away 256 sets of changeable system code - Plug and socket not included, and users can install other power cables into RC03

DIY ALARM KITS

	2 Zone PIR Alarm with IR Remote Kit			Security Alarm Panel	
	Code	PIR-3312K		Code	MEALM-4ZBM
	1 x 2 Zone PIR Alarm Controller. An infrared (IR) remote controlled passive, infrared intrusion alarm with wide detection coverage, $8 \times 12\text{m}$ 2 x IR Remote Control Keys. Infrared remote Arm/Disarm controller with 6 561 address code, 8m control distance, Home-Away-Off operations. It is also a panic button to trigger alarm in emergency, whether in armed or disarmed status. 1 x 12VDC Output Power Adaptor 5 Magnetic contacts (Door/Window Sensors) 1 x External Piezo Siren. Resets automatically after 1 minute, 108dB 30 meters of wire (2 pieces, each 15 meters)			Features 4-Zone Wired Alarm Panel - Compact, Low Cost System - Microprocessor controlled 4 x Hard Wired Zones - Full Remote Control (1 Remote incl.) 2 x Output Triggers - Zone Bypass Feature - Onboard charger with battery back-up 24hr Audible Panic 1 x Code Hopping Remote Unit	



Main unit connects with telephone

Wireless Auto-Dial Alarm System

Code	Features
RL-0503F	- Working range is 60m+ - Dial telephone or cell phone automatically when activated - All settings and recorded messages stored in case of power failure RL-R6 Remote Control - wirelessly turn unit ON or OFF RL-R2 Indoor Siren - will sound immediately when alarm is triggered RL-R7 Outdoor Siren - will sound immediately when alarm is triggered RL-R5 PIR sensor - detection 10m RL-R3 Magnetic Contact with built-in alarm RL-R1 Main Control Unit - can accommodate up to 38 accessories



Main unit with built-in GSM Module


6-Zone Wireless Alarm System

Code	Features
RL-0503C-D	- Working range is 60m+ - Dial telephone or cell phone automatically when activated - Adopts GPRS wireless transmission technology. It can dial telephone or send SMS automatically for alarm without telephone line, wirelessly arm/disarm the system and monitor audio from site - Voice recording function - Up to 38 accessories - Panic button is available - The system will call the saved 6 groups of phone numbers when activated

DIY INDOOR DETECTOR ALARMS

				
Code	123SK	135P	5200	436
Features	• Ceiling 360° motion detector alarm with remote control • Built-in alarm output up to 105dB • 9V battery operation (not incl.) • Optional-outdoor siren 120dB • Remote control	• Motion detector alarm with remote control • Motion sensor with up to 6 digit security code • 2-Pair magnetic • Infrared remote control with panic button • Built-in alarm output 105dB	• Dual motion detectors with magnetic sensor • 1 x wide range sensor • 1 x curtain range sensor • Built-in alarm up to 105dB with remote • Programmable codes • Panic button • 2 x magnetic contacts • 9V back-up and AC power adaptor	• 5-in-1 alarm • Box alarm • Personal alarm • Bicycle alarm • Door alarm • Travel alarm • Cable-lock with vibration sensor • Built-in alarm output up to 100dB • Panic button
				Features • Working frequency: 434Mhz • Working distance: ± 30m • Detection angle: 120° • Alarm volume: >100dB
Code	RL-9830	RL-9830RF2	RL-R10	
	1 x RL-R19 Sensor (Range: 3m 100dB) 1 x RL-R10 Remote	2 x RL-R19 Sensor (Range: 3m 100dB) 2 x RL-R10 Remote	Spare Remote	
	PIR LED Night Light	Automatic LED Night Light	3-IN-1 LED Power Failure Light	
				
Code	FL-A08B	335NL	236	
Features	• Power Supply: Battery operated 3 x AAA (excl.) • Sense Distance: 8~10m • Sense Angle: 160°	• With photocell sensor, automatically on at sunset, off at dawn • Long life LED	• When power failure automatically turn on super bright LED emergency light • With photocell sensor, soft LED night light automatically on at dark, off at dawn • Built-in rechargeable batteries for continuous use over 10hrs • Super bright LED torch • AC power indicate LED	

HOME SECURITY


	Magnetic Sensor Entry Alarm	Magnetic Sensor Entry Alarm	Glass Vibration Breakage Alarm	Door Wedge Guard	Sliding Door & Window Alarm
					
Code	S080N	S080K	S086K	S063	S062
Features	No tools installation, a built-in 80-85 dB alarm siren and is excellent for windows, sliding doors & cabinet protection. Operates on two button cell batteries (included).	No tools installation, a built-in 90-105 dB alarm siren and is excellent for windows, sliding doors & cabinet protection. Operates on two button cell batteries (included).	Can be used on any glass window or door and features no tools installation. Built-in 80-85 dB alarm siren. Operates with two button cell batteries (included).	Uses a contact plate or vibration for alarm activation and has a high output 110-112 dB alarm siren. Great for travelling. Operates with a 9 volt battery (included).	High output 110-120 dB alarm, a screw locking mechanism for sliding window security. Activated by vibration. Operates with a 12 volt battery (incl). Easy installation.
	Entry Protection Chime	Wireless Door Chime	Personal Safety Light	Detector	
					
Code	S082X	DC4101	MINI FLASH	SW-3003	
Features	Digital keypad on/of control, a built-in alarm siren and alarm or chime modes, it operates with 3 x AAA batteries (not incl). Instant or delay alarm options with detached magnetic sensors.	50m range. 256 codes to prevent interference. Power sources: Sensor 12VDC power or 1 x 6V battery (incl). Chime Unit: 4 x AA Batteries (not incl). 3 Chime options: 2 note chime, Bell tone, Westminster. Adjust. volume	Compact & modern design. Attracts attention from over 1km at night. Ideal for safety signalling during jogging, cycling, hiking, camping, etc. Size: 26(L) x 10(W) x 55(H)mm	Hand held Metal Detector (Body scanner). Battery operated 9V rechargeable 130mAh or 150mAh (not included). Battery charger: 9V 500mA (included)	

NIGHT-WATCHER MOTION SENSORS IP54

Supply Voltage: 230VAC RX7s Lights can be fitted		 Includes wireless camera transmitting up to 80-100m	Receivers for AEC-9336C-D	
Code	FS69-W	AEC-9336C-D		
Description Features	Motorised Floodlight • 3 x Passive Infrared sensors • Light activates for 3mins • Programmable functions for day and night • Detection 210° up to 10m • 9W CFL Daylight Lamp (incl)	24W Motorised Floodlight with camera • Built-in camera, 2.4GHz wireless SD card - storage up to 2GB max • Sensor 10m x 160° • Camera spec: 640 x 480 @ 10fps motion jpeg • Multi-sensor technology with 210° detection • Camera activates for 30secs • Night mode with light on at 3mins • Works with receivers: AEC711C, AEC707C, AEC752C	Code	Description
			AEC711C	Digital 2.4GHz wireless LCD monitor
			AEC707C	Digital 2.4GHz wireless TV receiver
			AEC752C	Digital 2.4GHz wireless USB receiver

POWER SERIES ALARM SYSTEMS

	16 Wired & 32 Wireless Zone Kit	8 Zone Hardwired Alarm Kit	16 Zone Hardwired Alarm Kit
			
Code	ACDC-DSC-16H16W-LCD	ACDC-DSC-8H-LED	ACDC-DSC-16H-LCD
	1 x 8 Zone Hardwired Control Panel	1 x 8 Zone Hardwired Control Panel	1 x 8 Zone Hardwired Control Panel
	1 x 8 Zone Hardwired Expander	1 x LED Keypad	1 x 8 Zone Hardwired Expander
	1 x 32 Zone Wireless Receiver	2 x Digital PIR Detectors	1 x LCD Keypad
	1 x LCD Keypad	2 x Magnetic Door Contacts	4 x Digital PIR Detectors
	4 x Digital PIR Detectors	1 x Power Supply	2 x Magnetic Door Contacts
	2 x Magnetic Door Contacts	1 x 12V 7Ah Backup Battery	1 x Power Supply
	1 x Power Supply	1 x 25W Siren	1 x 12V 7Ah Backup Battery
	1 x 12V 7Ah Backup Battery		1 x 25W Siren
	1 x 25W Siren		

	8 - 16 Zone Control Panel	8 - 64 Zone Control Panel	Wireless Repeater	Wireless Receiver
	Expandable to 16 hard wired or 32 wireless zones 	Expandable to 64 hard wired and/or 32 wireless zones 		
Code	22PC1808-NK	22PC1864-NK	22WS4920	22RF5132-433W
	• 8 On-board hardwired zones • 8 Partitions / 48 user codes • 4 On-board PGM outputs expandable to 14 • 500 event log • Supports up to 8 keypads	• 8 On-board hardwired zones • 8 Partitions / 95 user codes • 4 On-board PGM outputs expandable to 14 • 500 event log • Supports up to 8 keypads	• 433MHz / 868MHz • Up to 4 repeaters per system (requires 22PC5320) • 164 Wireless devices • Wall and cover Tamper • Quick Enrollment	• 433MHz / 868MHz • Supports 32 wireless zones • Up to 4 receivers per system (requires 22PC5320) • Supports up to 16 wireless keys • Wall and cover Tamper

	16 Zone LED Keypad	64 Zone LCD Keypad	Multiple Wireless Receiver
			
Code	22PK5516E1	22PK5500E1	22PC5320
	• Zone input • Backlit buttons on keypad • 5 programmable function keys • Dual FAP keys & AC Status ICON • Wall Tamper support • Buzzer and backlit button control	• Zone input • Backlit buttons on keypad • 5 programmable function keys • Buzzer and backlit button control • Dual FAP Keys • Wall Tamper support	• Multi-frequency support for combination of 868/433 MHz receivers • Compatible with 22PC1808 / 22PC1864 control panels • Can be used to connect up to 4 wireless receivers


WIRELESS DETECTION

	Door Contact	Vanishing Contact	Pet Friendly Detector	Smoke & Heat Detector
				Photoelectric 
Code	22WS4945W	22WS4975W	22WS4904W	22WS4936EU
	- Built in N.C. reed switch - External Contact Input 1 Lithium battery included - Case & mounting tamper detect	- Built in reed switch - Long-life lithium battery included - Case Tamper - Wafer-thin profile	- High traffic shut down - Fast / Slow sensitivity settings 1 Lithium battery included - Pet friendly up to 27kg	- Automatic drift compensation - Fixed heat & rate of rise detection - Built-in 85dB horn - Long life lithium battery included
	Lithium Battery	Evo Kit	LED Indicator	
				
Code	10LSH20	03EV-REC1E-5BUTT	03EV-REC LED	
	- Battery Lithium 3.6VDC - For wireless outdoor detectors	- DSC 5 button Evo kit 2 remotes & 1 receiver	1 LED with back plate - LED with back plate for Evo Kit	

BATTERY POWERED / WIRELESS READY DETECTORS

	Outdoor Detectors		Compact Outdoor Detector	Long Range Outdoor PIR	
	IP55 	IP55 	IP55 	IP54 	
Code	07VXI-R	07WXI-R	07FTN-R	07BX80NR	
	- Digital double layer detection 12m wide angle (90°) - Twin sensor PIR device 5 x adjustable detection areas 5 x adjustable detection ranges - Small animal tolerance function - Multi tamper detection protection	- Dual or Single Zone programmable - Up to 12m (180°) detection area - Adv. variable multi-area detection - Auto masking lens built-in - Pet friendly up to 45kg - Ultra low current consumption 3 - 9V Battery Powered (Lithium/Alkaline) excluded - Wireless transmitter excluded	- Selectable 5m/2m narrow ranges 190° horizontal rotation - Dual PIR for enhanced pet tolerance - Multi dimension analysis logic - Double conductive shielding - Intelligent 'AND' logic 3 - 9V Battery Powered (Lithium/Alkaline) excluded - Wireless transmitter excluded	- Variable 2 -12m x 600mm detection area on each side - Low current draw - Battery Saving Circuit - Advanced temp. compensation - Size judging function - Double conductive shielding 3 - 9V Battery Powered (Lithium/Alkaline) excluded - Wireless transmitter excluded	
	Outdoor AM Detectors		Photoelectric Beam	Dual Outdoor Infrared Beams	
	IP55 Pet friendly 	IP55 Pet friendly 	IP65 	IP55 	
Code	07HX40RAM	07HX80NRAM	07SL-350QNR	07AX100TFR	07AX200TFR
	- High Mount (2.5m - 3m) - Compensation logic - Active IR anti mask technology 12m / 85° detection pattern 94 detection zones - Vegetation sway analysis logic - Battery not included	- High Mount (2.5m - 3m) - Compensation logic - Active IR anti mask technology 24 x 2m detection pattern 20 detection zones - Vegetation sway analysis logic - Battery not included	100m range - Beam interruption adjust function - Triple tamper protection function - D.Q Circuit 99% beam blocking stability - Wireless ready - Batteries not included	- Range 30m - Triple tamper protection function 99% beam blocking stability - A.G.C circuit - Adjustable beam blocking time - Wireless ready - Batteries not included	- Range 60m - Triple tamper protection function 99% beam blocking stability - A.G.C circuit - Adjustable beam blocking time - Wireless ready - Batteries not included

HARDWIRED DETECTION SENSORS

	PIR Motion Sensor	Wide Angle & Long Range Detectors		Wide Angle Twin PIR																												
		IP54 	IP54 																													
Code	07FX360	07LX402C	07LX802N	07VXI-ST																												
	• 360° Ceiling mount PIR • Up to 12m diameter sensing • Mounting height of 2.4 - 3.6m • Improved EMI • Tamper detection • Patented multi focus lens	• Wide angle detection • 12x15m/120° detection pattern • Temperature compensation • Double conductive shielding • Day & night modes • Pet alley selectable	• Long range detection • 24 x 2m detection pattern • Temperature compensation • Double conductive shielding • Day & night modes • Pet alley selectable	• 12m wide angle (90°) twin PIR • Advanced SMDA target recognition • 5 x adjustable detection ranges • 5 x detection patterns • Small animal tolerance • Auxiliary input for second device																												
	Outdoor Detector	Compact Outdoor Detector	Long Range Outdoor Detector	Spacer																												
	IP55 	IP55 	IP54 																													
Code	07WXI-ST	07FTN-ST	07BX80N	07SP-2																												
	• Dual or Single Zone programmable (right/left) • Up to 12m (180°) detection area • Adv.variable multi-area detection • Advanced SMDA target recognition • Auto masking lens built-in • Pet friendly up to 45kg	• Selectable 5m/2m narrow ranges • 190° Horizontal rotation • Dual PIR Detectors for enhanced pet tolerance • Double conductive shielding • Multi dimensional analysis logic • Intelligent AND logic	• Variable 2 -12m x 600mm detection area on each side • Advanced temp.compensation • Size judging function • Double conductive shielding • Audible alarm function	• Spacer for 07BX80N																												
	High Mount Pet-Friendly PIR	High Mount Long Range PIR	IR Beam Detection - IP55																													
	IP55 	IP55 																														
Code	07HX40	07HX80N																														
	• High mount (2.5 - 3m) • Vegetation sway analysis logic • Dual signal processing • Intelligent AND detection logic • Compensation logic • 12m / 85° detection pattern • 94 detection zones	• High mount (2.5 - 3m) • Vegetation sway analysis logic • Double conductive shielding • Intelligent AND detection logic • Summer night compensation logic • 24 x 2m detection pattern • 20 detection zones	<table><tr><th>Code</th><th>Distance</th><th>No of beams</th><th>Length</th></tr><tr><td>28BS-IF-4 10M</td><td>10m</td><td>4</td><td>72cm</td></tr><tr><td>28BS-IF-4 30M</td><td>30m</td><td>4</td><td>72cm</td></tr><tr><td>28BS-IF-6 10M</td><td>10m</td><td>6</td><td>125cm</td></tr><tr><td>28BS-IF-6 30M</td><td>30m</td><td>6</td><td>125cm</td></tr><tr><td>28BS-IF-8 10M</td><td>10m</td><td>8</td><td>167cm</td></tr><tr><td>28BS-IF-8 30M</td><td>30m</td><td>8</td><td>167cm</td></tr></table> • Less than 40ms reaction time • Compatible with wireless and hardwired alarms		Code	Distance	No of beams	Length	28BS-IF-4 10M	10m	4	72cm	28BS-IF-4 30M	30m	4	72cm	28BS-IF-6 10M	10m	6	125cm	28BS-IF-6 30M	30m	6	125cm	28BS-IF-8 10M	10m	8	167cm	28BS-IF-8 30M	30m	8	167cm
Code	Distance	No of beams	Length																													
28BS-IF-4 10M	10m	4	72cm																													
28BS-IF-4 30M	30m	4	72cm																													
28BS-IF-6 10M	10m	6	125cm																													
28BS-IF-6 30M	30m	6	125cm																													
28BS-IF-8 10M	10m	8	167cm																													
28BS-IF-8 30M	30m	8	167cm																													
Hollow Enclosures for Photoelectric Beams																																
	c/w Light fitting Able to house up to 3 twin photoelectric beams 	c/w Light fitting Able to house most twin photoelectric beams 	c/w Light fitting Column enables the installation of up to 6 twin beams in any TX and RX combination 																													
Code	23CAV2	23CAV-W	23MALTA2																													
	• 180° Visual Sighting • Height - 100cm x Ø100mm • Durable aluminium structure • UV treated polycarbonate housing • Simple and discreet enclosure	• 180° Visual Sighting • Height - 58.45cm x Ø100mm • Durable aluminium structure • UV treated polycarbonate housing • Simple and discreet enclosure	• 180° Visual Sighting • Height - 185cm x Ø100mm • Durable aluminium structure • UV treated polycarbonate housing																													

BEAM DETECTION



Outdoor Infrared Beam Detection

Code	Outdoor Detection	Indoor Detection
ABH-100	100 meter	300 meter
ABH-120	120 meter	300 meter
ABH-150	150 meter	450 meter

Specifications

- 4 Beams: Infrared digital pulse
- Horizontal Angle adjustment (180°)



One Beam Infrared Detector - IP66

Code	AX-30KD
------	---------

Specifications

- Voltage: 9 - 16VDC
- White-light protection
- For external ranges up to 30m outdoors
- For gate automation
- Pre-selection access

Double Infrared Beam Detector - IP44

Code	Outdoor Detection	Height
FL-IR60	60 meter	170 mm

Specifications

- Weatherproof
- Double IR beam with infrared light source
- Supply volts: 10-28VDC
- Alarm Output: Relay output, AC/DC 30V 0.5A
- Work Temperature: -25 - 55°C
- Light Angle: Horizontal 180°±90, Vertically 20°±10



Infrared Beam Detector

Code	Outdoor Detection	Height
FL-IR250-3	5 meter	685 mm
FL-IR250-5	5 meter	1200 mm
FL-IR250-8	5 meter	1720 mm

Specifications

- 3/5/8 IR Infrared Beam Supply: 9-15VDC
- Detect Speed: 50 - 300ms (Adjustable)
- Alarm Output: Relay O/P, AC/DC 30V/10A
- Work Temperature: -25 - 55°C
- Light Angle: Horiz. 180±90, Vert. 20±10



Twin beams provide reliable perimeter security, minimizing false alarms from falling leaves, etc. Weatherproof, sunlight-filtering case for indoor and outdoor use. Easy installation with built-in laser beam alignment system.



Twin Photobeam Detectors - IP55 Supply: 10-30VDC (non-polarity)

Code	E960-D90	E960-D190	E960-D290	E960-D390
Max. range outdoor	30m	60m	90m	120m
Max. range indoor	60m	120m	180m	240m
Current	47mA	56mA	60mA	62mA
Interrupt Speed	50msec~700msec (variable)			
Alarm / Tamper Output	N.O./N.C. relay, 1A @ 250VAC / N.C. relay, 1A @ 250VAC			
Alignment Angle	Horizontal: ±90°, Vertical: ±5°			
Operating Temperature	-25° ~ 55°C			

MAGNETIC SWITCHES

Plastic



Code	MC-10(N/O)	MC-01(N/C)	IM-140	SM-207-5Q	SM-207-5LQ	S-1091B	S-102
	• Wide Actuating distance: 20mm • 100mA@35VDC • Operating distance: 15mm ± 5mm		• Flange mounted • Operating Distance: 16mm ± 5mm • N/C 150mA	• Magnet contact • Operating Gap 1" (25mm) • N/C Contact	• Magnet contact • Operating Gap 3/8" (10mm) • N/C Contact	• Zinc Alloy Housing, Chrome Plated • 2 Position Off/On • Contact Rating: 0.5@250VAC • Key removal in both 'On' and 'Off' positions • Each key switch uniquely coded	

Metal



Code	HO-03D	HO-03P	IM-136	IM-141	MC-02 (N/C)	IM-15
	• 1 C/O (500mA) • Armoured cable • Size: 111x45x12mm	• 1 C/O (500mA) • Armoured cable • Size: 111x45x12mm	• 20" (50cm) • Stainless steel armoured cable • Size: 106x38x10mm	• Magnet contact • Size: 106x38x10mm	• Mounting hole: Ø 9.5mm • 100mA@35VDC	• Anti-Tamper Switch • Voltage: 12VDC • Load current: 1.25A

HARDWIRED DETECTORS

Dual Technology Motion Sensors



Code	DT7225	DT7435	DT7450C
Max. Range	7.6m x 9m	11m x 11m	15m x 18m
Consumption	25mA	25mA	30mA
Voltage	9-16VDC	9-16VDC	9-16VDC
M.W Frequency	24.125GHz	24.125GHz	24.125GHz
Install Height	2.3m	2.3m	2.3m
Sensitivity	H/L Select	H/L Select	H/L Select
Dimensions	119x71x42mm	119x71x42mm	119x71x42mm
Pet Immune	No	Yes (45kg)	No
Alarm Output	NC (Energised)	NC (Energised)	NC (Energised)

- PIR and MW Detection
- Total view: 90°
- Anti-white light, Alternative LED-off mode
- PIR field of view: 22 long range
2 intermediate
6 lower range

Indoor Hardwired Motion Sensors

					
Code	22LC-100-PI	PIR-9236	LP-991	PA-476PET	PIR-9822
Type	Pet Immune 25kg	Dual Passive	General Purpose	Pet Immune 18kg	Dual Passive
Volts	8.2 - 16VDC	9 - 16VDC	8 - 16VDC / 5mA	8 - 16VDC / 18mA	9 - 16VDC / 15mA
Range / Angle	15m / 90°	3.6m high / 360°	12m / 120°	15m / 88.5°	15m / 110°
Size	92 x 63 x 40mm	Ø86 x 22.5mm	102 x 72mm	94 x 66 x 52mm	127 x 64 x 45mm
					
Code	CQ-86	FL-AC03	FL-AL7	FL-AC12	F102TWIN13/V
Type	Dual Passive	General Purpose	Glass Break & PIR	Glass Break	PIR & Microwave
Volts	12VDC / 16mA	8-16VDC/30mA	8-16VDC	8-16VDC	12VDC
Range / Angle	12m / 120°	12m/160°	12m/120°	3m(70-80dB)	13m/108°
Size	70 x 60 x 37mm	92 x 68 x 59mm	134 x 68 x 56mm	93 x 56 x 25mm	118 x 68 x 51mm

Outdoor Passive Detectors - IP54

Emergency / Egress Buttons

				
Code	DG85	LX-402	SS-075C-PEQ	HO-02
Type	Dual Passive	Outdoor	c/w 3 Stick Lables & mounting screws NO/NC (1A 12VDC)	White with Silver Label NO/NC Contact
Volts	9 - 16VDC / 30mA	10.8 - 13.2VDC / 25mA		
Range / Angle	11 x 11m / 90°	12 x 15m / 120°		
Size	176 x 83 x 66mm	141 x 75 x 53mm		


ALARM ACCESSORIES

Security Comms Cable (per 100m roll) - Voltage 12V



Code	Solid Conductor	Size (mm)	Code	Stranded Conductor	Size (mm)
WS04	4 Core Solid	0.4mm Copper	WST04	4 Core Stranded	0.22mm Copper
WS06	6 Core Solid	0.4mm Copper	WST06	6 Core Stranded	0.22mm Copper
WS08	8 Core Solid	0.4mm Copper	WST08	8 Core Stranded	0.22mm Copper
WS12	12 Core Solid	0.4mm Copper	WST12	12 Core Stranded	0.22mm Copper
WS20	20 Core Solid	0.4mm Copper	WST20	20 Core Stranded	0.22mm Copper

Cabtyre & Ripcord - Lengths 5m, 10m, 20m, 50m



WIR

Code	Solid Conductor	Size (mm)
W201-*	3 Core Cabtyre	0.5 x 3 Core
W401-*	White Ripcord 0.2	0.2mm Copper
W402-*	White Ripcord 0.4	0.4mm Copper
W403-*	White Ripcord 0.5	0.5mm Copper

*Add Length: 5M, 10M, 20M, 50M

*Specify colours: ○ WH(White), ● BK(Black), ○ C(Clear)

Clear Cable Glue Tube (50ml)



Code	CGL-AD90
Description	• Ideal for fixing wiring to nearly any surface • Use with any alarm cable


Sealed Lead Acid Battery - Maintenance Free



BC1

Code	Capacity	Size (mm) L x D x H	Terminal
SY1270	12V/7Ah	150 x 65 x 102	Lug
SY12012	12V/12Ah	151 x 98 x 102	Lug
SY12024	12V/24Ah	165 x 126 x 173	Lug

Clear Adhesive



Code	JT-ADH-BL-GCL
Details	Clear Adhesive
Size	50ml
Qty. per box	18

P3

SMOKE GENERATOR

Smoke Generator Unit



Code	WY-15
Operating Frequency	433.92MHz
Smoke effectiveness	30min, self extinguishing
Power Source	110V/220VAC
Spray time	55 sec / 5 times / 450cc
Dimensions (mm)	280 x 140 x 400L

Kit consists of

1 x smoke generator, 1 x key remote, 1 x cradle, 1 x manual, 1 x PIR, 1 x window sensor, 1 x chemical 450cc

Features

- Wireless or wired control
- Effective range 7 metres
- Smoke made of inflammable, non toxic substance
- Smoke consists of plant vapour causing no harm to the human body, furniture & electrical equipment

Optional Extras

Code	Description	Code	Description
WY-SMOG-RC	Key remote controller	JBS-100R 12VDC	Flashing light (DC12V)
WY-SSS-YW	Window sensor	KPS-112	Siren 110dB
WY-SSS-YP	PIR motion detector	WY-SMOG-CT	Counter (spray times)
TFAD091155	AC adaptor for PIR unit	FD-601-B02B	Software with USB cable
FG-004-02	Liquid 450cc bag	WY-SMOG-BU	Buzzer

Application

Security: On entry by intruder into the premises, the alarm is triggered & the smoke system is activated. The intruder will be unable to see any articles intended to be stolen and will leave the premises immediately.

OUTDOOR SIRENS WITH STATUS INDICATION IP65

For more sirens and beacons see pages 411-426



Code	IM-301	IM-303	IM-302
Voltage	10-15VDC / 400mA (max)	13.8-14.2VDC / 1550mA (max)	10-15VDC / 420mA (max)
Siren Output	115dB @ 1m	120dB @ 1m	115dB @ 1m
Timer	5 sec, 3min, 20min, continuous	5 sec, 3min, 20min, continuous	5 sec, 3min, 20min, continuous
Battery Back-up	No	Yes, 12V up to 1.3Ah	Yes, 7.2V up to 500mA
Dimensions (mm)	210 x 130 x 78	270 x 193 x 100	300 x 250 x 65

STAND ALONE ACCESS CONTROL



With doorbell button

Code	DK-9810D
Output	1 Relay Output @ 5A(NO/NC) 1 x NC Tamper. Collector Output 1 x NPN Transistor open
Mounting	Surface
Supply	12VAC/DC



15VAP-12VDC-T

Code	Description
DK-2882CARD	Extra cards for DK-2882
15VAP-12VDC-T	Adaptor Plug
- These keypads are self-contained digital access keypads designed for door strike and other access control applications in office and home security installations. - Single User Code and Multi-User Codes for operating the relay output.	

Stand-Alone Proximity Reader IP67

Code	PR-112S-A	Features - Sealed & weatherproof - Output relay 1W either timed (1 - 180s) or "toggle" mode - Buzzer for audible confirmation - Up to 100 cards can be programmed - User cards can be easily deleted - Up to 5 master cards can be programmed - c/w 10 cards included
Output	1 x Relay 1A@30V	
Mounting	Surface (Weatherproof)	
Supply	12VDC	
Code	PR-KISI-A	
	Additional user cards Sold in packs of 10	
Code	PR-K1K1-AQ	
	Key fob style Proximity Tags (Pack of 10)	



Stand-Alone Fingerprint Access Controller

Code	F-007
Output	Relay output 2A@12VDC
Mounting	Surface
Supply	12VDC
Features - Programming done via remote control or using manager fingerprint - Up to 120 users can be identified & allows for exit button - Gives alarm when door is propped open - No need to connect to PC to program	



Standalone Biometric Readers

			
Code	EA20	EAC300	EC300
Fingerprint	2000	5000	5000
User Capacity	200	500	500
Memory	50000 Records	100000 Records	100000 Records
Communication	RS485/ TCP/ IP & USB pen drive	TCP/ IP & USB Communication	TCP/ IP & USB Communication
Software	Stand alone with software	Stand alone with software	Stand alone with software
Screen Size	2.5" TFT Screen	3.5" TFT Touch Screen	3.5" TFT Touch Screen

ACCESS CONTROL

Standalone Biometric Reader

Power Supplies to be ordered separately	Fingerprint & Face Reader
 	
Code	ZK-MULTIBIO800-H
Face Templates	1500(1:N), 4000(1:1)
Fingerprint Temp.	4000
Transaction Log	100 000
RFID Cards	10 000
Communication	RS485 / TCP/IP / USB-Host
Wiegand Ports	Input & Output
Interfaces	3rd Party Locks, door sensor, exit button + Aux Input
Power Supply	12VDC 3A
Dimensions	188 x 88 x 63mm
SDK & Software	Standalone SDK, ZKAccess 3.5

Wiegand Door Controller

Power Supplies to be ordered separately	2 Door
	
Code	ZK-C3-200
No. of Doors	2 Doors
Readers Supp.	26bit Wiegand
Inputs	6 (2 Exit Device, 2 Door Status, 2 Aux)
Outputs	4 (2xLock, 2xAux OP)
Card Capacity	30 000
Transaction Log	100 000
Communication	TCP/IP & RS-485
Power Supply	12V DC 3A
Software	ZKAccess 3.5

Wiegand RFID Slave Readers

	IP65	IP64
 		
Code	ZK-KR601E	ZK-KR602E
Read Range	Up to 10cm	
Output Format	26bit Wiegand	
Buzzer	Yes	
Power/Current	6-14V / Max 70mA	
LED	Red and Green	
Input Ports	External LED Control & External Buzzer Control	
Size (mm)	86 x 16 x 86	86 x 20 x 86
Spare Cards	ZK-ID-CARD	
Spare Tags	ZK-ID-TAG	

ACCESS CONTROL

RS485/IP Biometric Access Control Panel		RS485 Slave Fingerprint Readers		
 Power Supplies to be ordered separately	2 Door Control 		IP65 	
Code	ZK-INBIO260	Code	ZK-F12	ZK-FR1500-WP
No. of Doors	2 Doors	Communication	RS485	RS485
No. of Readers	4 x RS-485, 4 x 26bit Wiegand	Function	Fingerprint & RFID Card Reader	Flush Mounting RFID Card Reader
Inputs	6 (2 Exit Device, 2 Door Status, 2 Aux)	Power Supply	12V DC 3A	12V DC 3A
Outputs	4 (2 x Lock, 2 x Aux OP)	Size	102 x 50 x 37mm	77.3 x 121.3mm
Card Capacity	30 000	Compatibility	INBIO Controllers, F16	INBIO Controllers or Standalone Fingerprint Devices
Fingerprint Cap.	3000			
Transaction Log	100 000			
Communication	TCP/IP & RS-485			
Power Supply	12V DC 3A			
Software	ZKAccess 3.5			

FINGERPRINT / RFID CARD / READERS

	Enrollment Reader	Readers & Access Control		Door Controllers
	Indoor 	Indoor 		
Code	AMA-U-BIO	AMA-T5-PRO	AMA-VF30	AMA-DC-E-1
Read Mode	Enrollment Fingerprint Reader	FP, Card, FP+Card	FP, Card, FP+Card PW+Card, FP+Card	Single door controller Input from two readers Comms: TCP/IP Opening Time: 1 - 600sec No. of Users: 20000
FP Capacity	—	1000	2000	
Card Capacity	—	1000	2000	
Record Capacity	—	50000	50000	
Software	—	Mi-Time Light (Incl)	Mi-Time Light (Incl)	
Power Supply (Not Supplied)	—	12VDC/3A With battery back-up	12VDC/3A With battery back-up	
Comms	USB	TCP/IP, RS485, Mini USB	TCP/IP, RS485, Mini USB Wiegand I/O	
Input	Connection for Egress control (Requires 1 x NO potential free contact)			
Output	1 x Relay C/O contact (12VDC/1A) can be used for Mag-Lock control			
Features	Access Control: Fingerprint Reader. Compatible with Mi-Time & Mi-Time Light software. Compact and portable with USB connectivity.	Access control, Fingerprint and RFID card reader. Easy user enrollment via master card or software. TCP/IP, RS485, Mini USB communication.	Full Time and Attendance functionality. Access Control, Fingerprint, RFID card reader and PIN Password. RS485, Mini USB slave, TCP/IP, Wiegand I/O communication.	

Accessory - Mi-Time Software (Full Package)

Code MI-TIME-*


* Add number of employees to code: 50, 100, 150, 250, 300

Note: Available for 350-10000 plus employees - please request quotation

- Annual licence fee based on number of employees.
- User Friendly - Intergrates into all major payroll packages.
- Unlimited shifts and rosters.
- Flexi / Daily / Weekly shift setup.
- Monthly / Weekly / Fortnightly / Over-time calculations.
- Leave management.
- Employee badge printing.
- Manual / Auto editing.
- Windows 7, XP & VISTA.

NEW

SMART DOOR LOCK

	Wi-Fi Fingerprint Door Lock	Bluetooth Fingerprint Door Lock	Bluetooth Fingerprint Door Lock	Wi-Fi Fingerprint Door Lock	Bluetooth Fingerprint Door Lock
					
Code	PST-HR01	F11S	KT-R10	KT-R15	F20
Operation	Fingerprint, ID Card, Password, mechanical Key and Smartphone APP	Fingerprint, ID Card, Password, Mechanical Key and Smartphone APP	Smartphone App, Fingerprint or Key	Smartphone App, Fingerprint, Key, Pin code, IC card	Fingerprint + PIN Code + Backup Key + Bluetooth /APP, Anti-peep virtual password, IC card
Power Supply	5VDC -USB charging port	5VDC -USB charging port	5VDC -USB charging port	5VDC -USB charging port	5VDC -USB charging port-type-C
Battery	4 x AAA batteries (not included)				
User Capacity	3 admin & 100 users	30 users	1 admin & 20 users	2 admin & 48 users	30 users
Door thickness	39.9mm - 100mm	35-68mm	38-55mm	35-55mm	35-55mm
Standard configuration	5050 Lock body (Inc.)	5572 mortise(Inc.)	5050 Lock body(Inc.)	Deadbolt latch (Inc.)	5572 mortise(Inc.)
Material	Aluminum Alloy+Acrylic	304 Stainless Steel	Zinc Alloy	Zinc Alloy	Zinc Alloy
Size (L x W x H)	240 x 60 x 21mm	190 x 80 x 30mm	149 x 27mm	148 x 62 x 30mm	70 x 80mm

ELECTRICAL DOOR LOCKS

	Electrical Door Locks		Electric Deadbolts		Power Supply
					
Code	EL-971B	EL-271-NO	EB-281	MB-280	15VAP-12VDC-T
Features	• Fail-secure • 12VDC 450mA rated current • Size(mm): 150(L)x25(W)x33(H) • Normally de-energised	• Fail-secure • 12VDC 450mA rated current • Size(mm): 160(L)x25(W)x31(H)	• Fail-safe (Doors open automatically once the power fails, locked when energised) • 12VDC operation • 900mA at start, 150mA at standby • 16mmØ • Stainless Steel Bolt	• Mounting bracket for upper glass and glass door • Stainless Steel • Size(mm): 205(L) x 58(W) x 46(H) • Glass thickness: 8-15mm	• Input: 230VAC • Output: 12VDC • 15VA unregulated • Plugs into 15A socket outlet


TURNSTILES & METAL DETECTORS

	Walk Through Metal Detector			Turnstiles - TS1000 & TS2000 Series		
						
Code	ZK-D1065S	ZK-D3180S	ZK-D4330	Code	ZK-TS1000	ZK-TS2000
Power Supply	85-264VAC	85-264VAC	100-240VAC	Power Supply	AC 220V/110V, 50/60Hz	
Working freq.	4KHZ-8KHZ	4KHZ-8KHZ	4KHZ-8KHZ	Working Environ.	Indoor/Outdoor (Sheltered)	
Sound Alarm	Yes	Yes	Yes	Rated Power	60W	
Detection Zones	6 Zone	18 Zone	33 Zone Standard	Flow Rate	25 - 48 Passage / Minute	
Sensitivity Control	✓	✓	✓	Housing Material	SUS304	
Sound/LED Alarm	✓	✓	✓	Pictogram Indication	Yes	
Auto Count	✓	✓	✓	Control System	Input controlled by dry contact	
Password Protect	✓	✓	✓	Size (mm)	980x520x280 + 500(Arm)	980x1100x260 + 500(Arm)

ELECTRICAL & MAGNETIC DOOR LOCKS & DOOR RELEASES

Electro Magnetic Locks

- Housing: Aluminium
- Dual Voltage:
12 or 24VDC
selectable by jumper



E-941DA-1200


Code	E-941DA-1200	E-941SA-1200	E-941SA-600
Power Dual Volts	12VDC/24VDC	12VDC/24VDC	12VDC/24VDC
Magnet Size	536 x 42 x 67mm	268 x 42 x 67mm	250 x 27 x 42mm
Armature Size	185 x 16 x 61mm	185 x 16 x 61mm	185 x 12 x 38mm
Holding Force	545kg	545kg	272kg
Supply ±10% (per door)	500mA@12VDC 200mA@24VDC	500mA@12VDC 250mA@24VDC	500mA@12VDC 250mA@24VDC
Temperature	-10°C to +55°C	-10°C to 55°C	-10°C to 55°C
Weight	10kg	5.0kg	2.0kg

Power Adaptor for 12 VDC:

Code: 15VAP-12VDC-T

How they work:

When power is applied to the magnetic lock, it turns on the unit's powerful built-in electromagnet. This electromagnet is attracted to the steel armature plate which is mounted on a door, holding the door fast against unauthorized entry. When power to the magnetic lock is turned off, the electromagnet releases the armature plate allowing the door to open.



Code


Z-Bracket



E-941S-1200/Z

E-941S-600/Z

L-Bracket



E-941S-1200/L

E-941S-600/L

U-Bracket

For Glass Door (9-13mm)



E-941S-1200/U

E-941S-600/U

Magnetic Door Release IP42

											
FSMD-B											
Code	24VDC	Wall Mounted (Metal Enclosures)		Wall Mounted (Plastic Enclosure)		Floor (Metal)		Universal (Metal)			
		FSMD-024-40	—	FSMD-024-50P		FSMD-024-50		FSMD-024-100			
Code	230VAC	—	FSMD-240-40	—		—		—			
Mounting		Wall	Wall	Wall		Floor		Both (300mm arm)			
Nominal Current		75mA	9mA/2W	7mA/1.6W		75mA		100mA			
Circuit Configuration		Solenoid	Solenoid	Solenoid		Solenoid		Solenoid			
Holding Force		40Kg/390N	40Kg/390N	50Kg/490N		50Kg/490N		100Kg/980N			
Housing		Metal base and cover		Plastic base and cover		Aluminium		Aluminium & Steel			
Manual Release		Yes									
Temperature		-10°C to +40°C									
Weight		0.84Kg	0.93Kg	0.50Kg		0.90Kg		1.8Kg			
Accessories		Bracket for floor mounting FSMD-B				—		—			
Power Supply		15VAP-24VDC-T	—	—		15VAP-24VDC-T					

ELECTRIC FENCING

Energiser Wizards



Code	Description
E-WIZ2	2 Joule Energiser 7400V, B/B
E-WIZ4	4 Joule Energiser 8000V, B/B

Druid



Code	Description
DRUID13-LCD	3 Joule Energiser LCD Screen 9000V, B/B, 3km
DRUID15-LCD	5 Joule Energiser LCD Screen 9000V, B/B, 5km
DRUID18-LCD	8 Joule Energiser LCD Screen 9600V, B/B, 10km

Solar Petstop - DIY Kit 24m



Code	AA-PET/ KIT
Description	1 x Petstop Energiser 1 x Solar panel 1 x Mounting Bracket 8 x Fibre Glass Poles 24 x Spring Clamps 200m x Poly Wire 1 x Warning Sign 1 x Galvanised Earth Spike Can also be installed on a wall top



Merlin

Code	Description
E-MER4	4 Joule Energiser - Including: Keypad, 800V, B/B
E-M18S/V1	8 Joule Single Zone Energiser 140V, 10km, 9300V, B/B
E-M28S/V2	8 Joule Dual Zone Energiser 120W, 2 x 5kW, 9300V, B/B



Keypads

Code	Description
EE-MKP	Merlin Standard Keypad
EE-M1Z2GK	Merlin 1 Zone - 2 Gate Keypad
EE-M2ZKP	Merlin 2 Zone - 2 Gate Keypad
EE-DR.LCD/KP	Druid Keypad - LCD Energisers

ELECTRIC FENCING ACCESSORIES



Flashing Beacon

Code	JBS-100R-230VAC
Description	Xenon Strobe Beacon
Features	80FPM, 15W, 800mA



Siren Speaker

Code	KPS-100T
Description	ABS Siren Speaker
Size	15W
Frequency	8Ω

In-Line Gate Contacts



EA-SGC/SS



EA-SGC07

Code	Description
EA-SGC/SS	Inline Sliding Gate Contact Single Pole
EA-SGC07	Inline Sliding Gate Contact 2 Pole
EA-SGC07ZB/HDG	Z-Bracket for EA-SGC07



Stay Clamp

Code	EA-RAT
Description	Stay Clamp Rubber
Size	10 x 12mm



6mm

8mm

Line Clamps

Code	Description
EA-LC6	6mm Line Clamp
EA-LC8/MG	8mm Line Clamp



Ferrules (100 per packet)

Code	Description
F06	6mm Tinned Copper
F10	10mm Tinned Copper
EA-F6AFT	6mm Aluminium



TL-FS Fence Scope

Code	Description
TL-FS	Directional DVM Fault Finder
TL-FSTP	Carry Pouch

ALUMINIUM BOX ENERGIZER ENCLOSURES




Code	ENC-ALU-M
	- Vented 610(h) x 450(w) x 260(d)mm - Medium capacity to house an energizer, solar regulator and a deep cycle battery

Code	ENC-ALU-L
	610(h) x 800(w) x 300(d)mm - Large capacity to house double energizers, solar regulator and deep cycle batteries - Available in shock box version (ENC-SHBOX)



Application Example

ELECTRIC FENCING



Insulators & Tensioners




Code	Description
EI-NOB	Nail on insulator - Black
EI-BFBB	Bobbin - Flat bar - Black
EI-YB	Insulator - Y Standard - Black
EI-OB	Insulator - Omega with clip -Black
EI-STB/R	Strain ultra insulator - Black
ES-CNT	Comp spring-S/s silver nylon. Std Black
ES-CNTHB	Comp spring hybrid. S/s silver. Standard
ES-DT/MN	Black mini nylon tensioner Black
ES-H/LT	Spring hook S/S - large tail
ES-CTNTBB	Combo tensioner hybrid - Black B/b
ES-HK/EP	Free standing - S hook
ES-CTS	Combo tensioner standard
EA-EAN/L	Earth spike copper 1.2M
EA-LID2	Double Pole Lighting Inhibitor/Diverter

Accessories


	SR-FL/HVL4		EA-WRS2/N
Code	Description		
SR-FL/HVL4	Fence light, High voltage, Dual stage		
EA-WRS2/N	Electric Fence Warning Sign		

Wire & HT Cable



Code	Description
EW-TBB/5KG	Babybraid - Stranded Galv/wire 1.2mm A Grade 5kg Roll
EW-G2.24	Galvanized wire 2.24mm/50kg - 1650m roll
EW-AL16	Aluminium wire 1.6mm - 1000m/4.88kg
EW-AL16S	Aluminium wire stranded 1.6mm - 1000m
EW-TSS304/8	Stranded stainless steel wire 1.2mm - 800m roll
EW-TSS304/16	Stranded stainless steel wire 1.2mm - 1600m roll
EH-3BS100	HT Cable - Black - 3core / 100m slimline
EH-4BS100	HT Cable - Black - 4core / 100m slimline
EH-AS100	HT Cable - Black - Aluminium 100m
EH-BS030S	HT Cable - Black - slimline 30m
EH-BS100S	HT Cable - Black - slimline 100m
EA-BW/1.8x100HD	Bridging wire 100mm HDG
EA-BW/1.8x200HD	Bridging wire 200mm HDG
EY-1LOOP	Free standing inline loop
EY-1LOOP/EL	Free standing earth loop

Brackets & Stays



Code	Description
EF-6BA	Flatbar 6W Black Angled
EF-6BF	Flatbar 6W Black Straight
EF-6WA	Flatbar 6W White Angled
EF-6WF	Flatbar 6W White Straight
ESQ-6BF	SQ tube 20*20*1, 1.6mm-6W Black Straight
ESQ-6BA	SQ tube 20*20*1, 1.6mm-6W Black Angled
ESQ-8BA	SQ tube 20*20*1, 1.6mm-8W Black Angled
ESQ-8BF	SQ tube 20*20*1, 1.6mm-8W Black Straight
ESQ-6WA	SQ tube 20*20*1, 1.6mm-6W White Straight
ESQ-6WF	SQ tube 20*20*1, 1.6mm-6W White Angled
ESQ-8WA	SQ tube 20*20*1, 1.6mm-8W White Straight
ESQ-8WF	SQ tube 20*20*1, 1.6mm-8W White Angled
ER-6B	Round bar 6W Black
ER-6W	Round bar 6W White
ESTB	Stay 600mm Black
ESTBL	Stay 750mm Black
ESTW	Stay 600mm White
ESTWL	Stay 750mm White

NEW

GATE MOTORS

DTS Gate Motors

				
	Code	DTS-512LIT-KIT	DTS-AFRI500	DTS-512ML-OBT-KIT
	Voltage	230VAC at Gate	230VAC at Gate	230VAC at Gate
	On Board PSU	Yes	Yes	Yes
	Max Weight	500kg	500kg	600kg
	Max Speed	18 meter per sec	22 meter per sec	22 meter per sec
	End Limits	Spring	Spring / Magnetic	Magnetic
	Battery Back-up	Onboard	Onboard	Onboard
	Usage	Domestic	Domestic	Complex entry/exit
	Gate Direction	Selectable	Selectable	Selectable
Supplied Remote	2 x 60TX4	-	2 x 60TX4	
Nylon Rack	Not Supplied as part of kit -- Order separately See below DTS8489 x 2			

DTS Gate Motor Spares

Nylon Rack	DTS-8489	DTS-8489	DTS-8489
Cover	DTS-COVER-B	DTS-COVER-B	DTS-COVER-BU
Main PCB	DTS-PCBLIT	DTS-PCB512-150	DTS-PCB512-150
PCB Charger (PSU)	DTS-CHA1215	-	-
Battery	SY1270	SY1270	SY1270
Motor Brushes	DTS-BRUSH	DTS-BRUSH-150	DTS-BRUSH-150
Power Pack	-	-	ETDCSPS
Transformer	TRAECO	-	-
Magnetic Actuator Set	DTS-MHS	DTS-MHS	DTS-MHS

ACCESSORIES

Loop Detector

Code LOOPDE

- 4 Selectable exit times
- 4 Selectable sensitivity ranges
- Status indicating LED
- Condition monitor (open/short)
- Hi/Lo Frequency selection



Requires 20m silicon cable (not supplied) formed into 4 loops (for cable see Pg 261)

Mechanical Fittings



Galvanised theft resistant bracket

DTS-512/624-BRACKET

Code Hopping Receivers



DTSRX

DTSOCTO

Code	Description
DTSOCTO	5 Button key ring remote 434 MHz
DTSRX1	1 Channel receiver 434MHz
DTSRX3	3 Channel receiver 434MHz
DTSRXCONDO	1000 User receiver 434MHz
• Selectable Pulse or Latch mode	• User Friendly
• Visual indication of full memory	• Range
• High sensitivity	

GATE MOTOR ACCESSORIES

Complex Gate Receiver



COMPLEX-RXV3

Code hopping receiver
400 remotes, 2000 events

Repeater c/w Power Supply



RPT800P

Code hopping encryption & compatibility, 400 memory locations, Range $\pm$ 800m

Transmitters




MB3000P

Complete mimic base unit



WISIMO

GSM Communicator for Mimic base



14CHR-V2

14 Channel Receiver Decoder

Remotes (Transmitters)



TX1

TX2

TX4 / DTX4

TX6

Code	Description
TX1	1 Button key ring Code Hopping Transmitter
TX2	2 Button key ring Code Hopping Transmitter
TX4	4 Button key ring Code Hopping Transmitter
TX6	6 Button key ring Code Hopping Transmitter
DTX4-403	4 Button duplicator remote. 403Mhz
DTX4-433	4 Button duplicator remote. 433Mhz

1, 2 & 3 Channel Receivers / Transmitters



RX

S4

Code	Description
S4	4 Channel stand alone Code Hopping Transmitter - 2KM line of site
RX1-150	1 Channel Code Hopping Receiver 150M
RX2-150	2 Channel Code Hopping Receiver 150M
RX1-500	1 Channel Code Hopping Receiver 150M
RX4-500	4 Channel Code Hopping Receiver 150M

WIRED & WIRELESS RF TRANSMITTERS & RECEIVERS

Wired Transmitter

Code SK-939TDWS-B

- Powered by internal/external battery
- Operates up to **170M**
- Over 68 billion possible codes
- LED transmission indicator
- Includes 12VDC alkaline battery
- Wiring: 2 wires (200mm) for N.O. switch input, 2 wires (200mm) for 12VDC power input
- Frequency: 433.92MHz



Receiver



Dipole Antenna for Extended Range



Code	Description
SK910R-4	1 Channel
SK910R2-4	2 Channel
SK910R4	4 Channel

Code	SK-93ERSD
Frequency:	433.92MHz
Plugs into Board Connector on Receiver	
Extended range up to 200m for SK910R/R2/R4	

1 & 2 Channel Transmitters


Code	Description
SK-939TS1S	1 Channel
SK-939TS2S	2 Channel

- Operates up to **170M**
- Over 68 billion possible codes
- LED Transmission Indicator
- Includes 12VDC Alkaline Battery




Typical Applications

Make Push-Button Wireless



Convert Sensors into an Entry Alarm System



2 & 4 Channel Transmitters


Code	Description
SK-919TP2H-N	2-Button Transmitter fixed code
SK-919TP4H-N	4-Button Transmitter fixed code
CR2016/5	Spare battery (CR2016)



Features

- Operates up to 160m (500ft)
- Over 68 billion codes possible
- Includes visor and belt clip
- Includes 2 x 3VDC lithium batteries
- Frequency 433.92MHz

POWER SUPPLY/CHARGER



- Regulated and filtered output voltage
- Short circuit protection
- Built-in backup battery charger
- Switches to backup battery automatically in the event of power loss
- Fused protection for battery charger
- Input AC Voltage required for 6VDC (12VAC), 12VDC (16VAC), 24VDC (24-28VAC)
- Transformer selection $P = V \times I$ (for 2A @ 16VAC = 2x16 = 32VA) use 40VA standard VA
- Transformer excluded (see page 77)

MULTI-FUNCTION TIMER MODULE



- Timer can be set from 1 second to 60 minutes
- Positive or negative trigger on power-up
- Relay can be programmed to activate at the start or at the end of the timing cycle
- Relay can also be set to activate for one second at the end of the timing cycle
- Programmable for pulse (flash) or steady on
- Reset function for manual reset of timing cycle
- LED indicates relay is energised

Code	DC Voltage	Current (continuous)	Current (peak)
ST-2406-2A	6, 12, 24	1.5A	2.0A
ST-2406-3A	6, 12, 24	2.5A	3.0A
ST-2406-5A	6, 12, 24	4.0A	5.0A
ST-2406-7A	6, 12, 24	7.0A	7.5A

Code	SA-025
Relay Contact Ratings	8A @ 120VAC/24VDC
Supply Voltage	12/24VDC (auto sensing)

NEW

GATE ACCESSORIES



Code	GOOSENECK-STAND	DTS-RS-UNIV	DTS-RSG-UNIV
Description	Gooseneck stand for intercom	Rainshield	Grid for Rainshield

SMART WIFI GATE REMOTE CONTROL

MyGateRemote Controller

Code	MG-REMOTE
Supply Voltage	12-24VDC
Outputs	2 x Relay Outputs C/O
Relay Rating	30VDC/250VAC 10A
Size (LxHxD)	110 x 27 x 43mm
Wifi Range	80m (Line of Sight)



Smartphone control for your gates/doors/locks/lights with a wifi device. Control the connected device via the free to download iOS or Android app. Uses very little data so costs are extremely low. Multiple users can share access. 2 Outputs allow for full opening or pedestrian opening.

- Can be controlled from anywhere with web access
- Free app for Android and iPhone
- Share Control with Multiple Users
- Easy to use and very secure
- No more security risks caused by lost or copied remotes
- Create entry tokens for friends & family
- Control staff access and check entry/exit times
- Full audit of entry/exit available



App: MyGate

Mobile phone
not included



KEYPAD REMOTE

Wireless Access Control Keypad

Code	MEKPD-01
------	----------

A durable, quality keypad designed to provide security access to a restricted area. Access is gained by entering a valid code. Up to a thousand codes can be stored in the unit's non-volatile memory. "Token" codes can be added allowing the user only preset number of activation, after which the code is deleted. User can be learned into a receiver compatible to the remote setting selected.

Features

- 1000 unique codes
- Backup memory module
- Integrated movement sensor
- 15 Channels
- Selectively add and delete user codes
- Easy installation due to no wires required
- Fixed and variable code length modes available
- Panic, duress, wrong code alarm functions

Specifications

- Supply Voltage: 3V – 2 x AA (not incl.)
- Housing Material: ABS
- Output Pulse Range: 1-255sec adjustable or latched
- Token Codes: 1-254 Activations
- Frequencies: 433MHz and 403MHz
- Distance 433MHz and 403MHz: ~40m
- Compatibility: Sentry, Centurion, ET (old), Sherlotronics, QD



GSM INTERCOM




The GSM Intercom module connects up to a standard existing intercom entrance/gate unit. This enables the intercom to dial to the tenants cellphone or landline. Managed over the internet via free - <https://cellswitch.accentronix.co.za>

Code	Users
GSMIN-100	Up to 10 000

Features

- Uses any contract/pre-paid simcard
- Dials to tenant's cellphone or landline
- Open up to 2 gates with your cellphone
- Secure online programming
- SMS fault reporting
- 2 Digital inputs to monitor power & gate status
- You are always 'home'
- Access control reports by email

Accessories

			
Code	GSM-RAIN SHIELD	GSM-PSU	GSM-PSU-BUP
Description	Stainless Steel Shield Intercom cover	12VDC 1A DIN Mount	13.5V PSU + 1.4Ah DIN Mount Surge Protected

WIRED DOOR CHIMES

*Please note all 8V chimes exclude transformers, please see page 802

DNU & GNU items exclude 3 x R6 1-5V batteries

zamel *get*

230V Type
with built-in
transformer




Code 230V	GNS-921	-	DNS-972-N	-	GNS-976-N	GNS-943	DNU-912-N	-
Code 8V	*GNT-931	*GNT-224	-	*DNT-911-N	-	-	-	GNU-913-N
Description	Bim-Bam Chime	2-Tone chime vivo	Tres Chime	2 Tone Chimes	Duo Chime	Duo Chime	16 Melodies	3 Tone Chime
Size (mm)	136 x 106 x 42	205 x 126 x 42	160 x 110 x 42	160 x 110 x 35	160 x 98 x 35	130 x 106 x 42	140 x 100 x 47	140 x 100 x 47
Tone	Bim-Bam	Bim-Bam/ Long Ring	3 Tones	2 Tones	Di-Do	Two-Tone	16 Choices	3 Tones
Sound Level	85dB	85dB	90dB	84dB	81dB	72 - 82dB	84dB	83dB

230V Type
with built-in
transformer



Code 8VAC	*GNU-209							
Code 230V	-	GNW-223	DNW-208	GRS-941	DNS-206	DNS-001		
Description	Westminster Chime	2 Tone Chime Turbo	Largo Chime	Pipe Chime	Traditional Bell	Bowl Bell		
Size (mm)	140 x 100 x 45	205 x 126 x 42	200 x 145 x 55	917 x 230 x 55	140 x 105 x 60	118 x 66 x 37		
Tone	8 Tones	Bim-Bam/Long Ring	Bam-Bam/ Long Ring	2 Tone	Electronic Bells	Electronic Bells		
Sound Level	76dB	85dB	85dB	82dB	90dB	82dB		

B&S
SUNNYBELL



Code	ST-3234T	ST-3239T	ST-3248T	*ST-3239B
Size (mm)		170 x 105 x 49		170 x 105 x 49
Power		230VAC Direct Connected with 230/8VAC 1A Transformer built-in		Battery 4 x Size 'C' or 8VAC supply. External Transformer required

T1

Bell Transformers • Double wound, **IP20** • DIN mounting



Code	Input volts	Output volts	VA
T-87	230V	8V	8VA
DT10212	230V	0-12V 0-12V (0-24V)	10VA
DT10612	230V	0-6 V 0-6V	10VA
DT15212	230V	0-12V 0-12V (0-24V)	15VA
DT15612	230V	0-6V 0-6V	15VA

BELLS / CHIMES PUSH BUTTONS



Code 230V	PDJ-213	PDP-970	PDM-231	PDB-234	PDM-232	PB-03	PB-04	PB-06	PB-09
Size (mm)	80 x 21 x 33	46 x 60 x 14	70 x 30	100 x 25	87 x 30 x 30	85 x 20	54 x 25	74 x 32	70 x 32

WIRELESS DIGITAL DOOR CHIMES

 EU12302.1					
Code		ST-59	ST-60	DRS-982	ST-1005
Transmitter	In line of site	100m		150m	100m
Range:	Through walls	80m		100m	80m
Radio Frequency		433.92MHz		434MHz	434MHz
Sound Level		82dB		85dB	10-30dB, 60-85dB
Call Ringing		1-Tone	Ding-Dong	Ding-Dong	36 Melodies
Chime (Receiver)		Adaptor 230/12V 300mA (incl.). Spare Code: EU12302.1 or 3 x size 'C' batteries (not incl.)		2-Pin Euro plug	3 x AA size batteries not included
Power supply		1 x 12V battery (included). Spare Code: WIR-12B		-	1 x 12V 1NC (Spare AC531)
Call button power supply					
Size (mm)		165 x 122 x 55	170 x 135 x 58	160 x 66 x 90	140 x 80 x 20
Additional Transmitter (call button)		ST-11	ST-11		

Wireless Door Chimes

 ML-8300 - Wireless combination door chime - Additional socket outlet on chime receiver offers multiple uses - Spare bell push button IP65 Code: MLT-7100 - Range 70m line of sight	 ML-7100 - Just plug and use - Flashing LED indicator for impaired hearing - Spare bell push button IP65 Code: MLT-7100 2 pin Euro Plug - Range 70m line of sight
--	---



Vibrating & Flashing Doorbell

Radio

Code **SSG-MF**

Includes

- 1 x Portable Vibrating Receiver
- 1 x Push Button Transmitter
- 1 x Plug-in Doorbell Chime
- c/w Batteries

Features

- 52 Ring tones | 4 Level vol. control
- 300m range in Open Air
- Receiver Supply 3V (2 x AAA)
- Transmitter Supply 12V (1 x 23A)
- Spare Batteries: **98111**, **AC531**

DIGITAL DOORPHONE KITS

	Wireless Devices		Wired Devices	
				
	Code	RL-0510	RL-0510B	RL-3203AAA
	Description	1 x Wireless Door Phone 1 x Wireless Door Station 1 x Power Supply	2 x Wireless Door Phones	1 x Door Station 3 x Indoor Phones
	Features	2.4GHz digital transmission - Dual-way inter-communication - Clear talking voice - Maximum working distance is 200m - AC Power Adaptor: 220-240V 50Hz AC 9V (incl.)		Features 2-Wire connections - Inter-communication - With unlocking function - Working Distance: 100m - DIY Assembly & High quality sharp clear voice - Anti-oxidation, wearable aluminium outdoor unit
			Features - Digital transmission for sound signal - Adjustable volume of melodies - Anti-interference - Inter-communication between indoor & outdoor unit - Adaptor included - Wired 2-way	



WIRED COLOUR DOORPHONE KITS WITH MONITORING CAMERA

Code	RL-037MP	RL-06C	RL-08M	RL-C7C
Description	1 x 7" Video Monitor 1 x Door Station 2-Wire Connection - Press call button to take picture - Night Vision	1 x 7" Video Monitor 1 x Door Station	1 x 8" Video Monitor 1 x Monitoring Camera 1 x Door Station	1 x 7" Video Monitor 1 x Monitoring Camera - Motion recording with SD Card to save memory - Clock and calendar function
Features	Electronic unlock mode, 8-Chord melody ring options, brightness, contrast & volume adjustment, 15m cable & power adaption, waterproof and damageproof cameras			
Code	RL-037M	RL-SD7F	RL-06MID	
Description	IP44 Waterproof 7" TFT Colour Screen - Night vision - Enclosed a switch power supply and 15m cable for DIY installation 1 x Power supply (230V)	- Works as video doorphone, invisible recorder, digital clock & perpetual calendar - Auto-recording onto SD card for outside moving objects only - Brightness, chroma and volume adjustable 8-Chord melody ring options - Night vision	17mm ultra-thin indoor unit - ID unlocking and electric controlled unlocking 7" TFT Colour Screen - Up to 100 user cards can be added to this system 1 x Power Supply (230V) 5 x user, 1 x delete & add card - Spare Card: RL06-CARD	

STAND ALONE WIRED VIDEO DOORPHONE KITS

				Spare Power Supplies	
Code	RL-3TV06A	RL-3TVP2-1		Code	RL-A1
Description	• 3 x 7" Video Monitors • 1 x Door Station • Power Supply (230V)	• 2 x 7" Video Monitors • 1 x Door Station & Indoor Phone • Power Supply (230V)			• Input Voltage: - 110 - 240VAC • Output Voltage: - 13VDC • Output Current: - 1200MA
Features • Hands-Free Communication • 8-Chord Melody Rings • Brightness, Contrast & Volume Adjustable		• 15m Cable & Power Adaptor • Night vision • Inter-communication between indoor units			• Input Voltage: AC 100-240V • Output Voltage: DC 12V • Output Current: 2000mA

2 Video phones for 2 Families

							
Code		RL-2A037		RL-2D06P2		RL-2TV06A	
Description		• 2 x 7" Video Monitors & 1 Door Station • 1 x Power Supply (230V) • High definition CCD Camera • Electric-controlled unlocking • Waterproof		• 2 x 7" Video Monitor & 2 x Door Stations • 1 x Power Supply (230V) • High definition CCD Camera • Electric-controlled unlocking • Waterproof		• 2 x 7" Video Monitors & 1 x Door Station • 8-Chord melody ring options • Waterproof, inter-communication, anti-oxidation • Hands-free • Night vision	

	Code	RL-2A10G
Description	- Suitable for two families - Waterproof and durable aluminium alloy outdoor unit - TFT colour screen - Night vision - Electric-controlled lock release - Easy installation for DIY market	

DIGITAL DOOR VIEWERS

A High-Tech "must have" gadget. Why just keep up with the Jones' when you can see if they have arrived (after you!)




Digital Peephole Door Viewer

Code	PHV-350
Description	- Sensor: 300,000 pixels - The display will stay on for 8 seconds - Press monitor button and the display will turn on - Press call button, when the LED light turns on the door chime will ring at the indoor display
	7" colour TFT display - Peephole barrel: 12-30mm - Fits any door 35-65mm

BASIC DOOR ENTRY KITS

legrand		Accessories			
Code	LG369580	LG369596	LG369400	LG369505	LG369220-KIT
Consists of	1 x Video Monitor + 1 x Outside station	Outside station with colour camera	External Colour Camera	Spare Inside station	1 x Video Monitor + 1 x Outside station
No. of Wires	4 wire system				2 wire system
Display	Colour 7"				Colour 7"
Ringtones	12				3 x MP3 melodies
Functions	Call, Intercom, Door-Lock				Call, Intercom, Door-Lock
Expandable	1 x Outside station or 1 x Camera + up to 5 x Inside stations				2 x colour displays
Spare Monitor	LG369585				LG369225



WIRELESS VIDEO DOOR ENTRY

Portable Colour Wireless Video Doorphone IP54			
Code	RL-0825AB	RL-0807AB	
	2.4" Colour Video Doorphone 2.4GHz operating frequency - Operated by lithium battery and external adaptor 230VAC (included)	- Wireless video doorphone - Wireless unlocking function - Wireless recording function - Auto-recording into SD card	
	- Distance: 50-70m - Dual-way intercommunication - Camera: CMOS - Size: outdoor: 126x93x34mm indoor: 102x66x17mm	- Video recorder, digital clock, and perpetual calendar all in one - SD card instead of DVR for smaller size, higher performance	

Wireless Palm Baby Monitor

Code	Description
ZT-822E	2.5" LCD Palm size Wireless Monitor

Features

- Small palm sized receiver for mobile usage
- 2.5" LCD screen with 480 x 234 resolution
- Rechargeable Li-Battery in receiver, enables at least 2 hrs continuous operation
- 380TV lines sharp picture display
- Built-in microphone in camera and speaker in receiver for audio monitoring
- 100m transmission distance (line of sight)

NEW

SMART WIRELESS DOORBELL IP54



Indoor Chime
Included



Microphone



WiFi
Control



App
Control



Speaker




Decibel
Alarm




Remote
Switching

WiFi Video Doorbell

Code	Description
MK-1C-KIT	- Power Supply: 5VDC/1A (not included) 1080P Full HD Video Quality • 122° Field view - Cloud Storage for motion detected recordings - Includes Rechargeable batteries (18650) - up to 3500mA - MicroSD card up to 128GB 2-way audio between phone and camera




Subscribe



NEW

WIRELESS DOORBELL AND MONITOR



- Supports remote call
- Microphone for duplex talk
- Supports PIR Motion detection
- Night vision



1MP/720P Video Doorbell with 4.3inch monitor

Code	US-PHR9
Display size	4.3inch
Video Resolution	1MP/720P
Lens Focal Length	3.6mm
View Angle	160° wide
Battery	5000mAh Lithium



App
Control



WiFi
Control



Voice Control



Speaker



Remote
Switching




Share Control
with Others

NEW

SMART VILLA VIDEO INTERCOM SYSTEM



TC-5000MH-18B



TC-3000DA-X1

Indoor Monitor

Code	TC-5000MH-18B
Display	10inch Capacitor Touch Screen, 1280*800P
CPU	64bit 4 core Cortex-A53
Operating System	Android 6.0.1
Memory	1G RAM
Camera	HD 720P
Communication	RJ45 (TCP/IP)
Expanded Port	8CH Alarm Port,SD Card Slot (inside)
Power Supply	12VDC/1A(incl.)
Dimensions	258.6 x 167.2 x 15.1mm
Installation method	Indoor wall mounting

Digital Door Phone

Code	TC-3000DA-X1
Camera Resolution	720P
Supply Voltage	12VDC/500mA
Communication	RJ45, Pulse Unlock
Dimensions	90 x 135 x 33.5mm
Installation method	Wall mounting



App
Control



WiFi
Control



Remote
Switching



- WiFi Connect to Internet
- Support Up to 4 Indoor monitors and 2 Outdoor Units
- Digital TCP/IP Intercom
- High Strength Acrylic Panel with Metal Frame
- Intercom Call to Resident with built in Speaker Stereo 16bit
- Pre-installed ACDC Smart App

PROFESSIONAL TWO WAY RADIO PMR 446

Professional Radios

Common Features

Monitor, Squelch, Programmable by PC.
• Transmission Power: ≤ 500mW ERP

- Robust Aluminium Chassis
- Vocal low battery indication
- SCAN



NEW



Code	BR02	G15
Channels	PMR446 8 + 8 pre-programmed	PMR446 16 + 16 Pre-programmed
Tones	38 CTCSS / 104 DCS	50 CTCSS tones + 105 DCS
Battery	1800mAh Li-Ion	1600 mAh Li-ion
Autonomy 5/5/90	Up to 21hrs	Up to 21 Hrs
Dimensions (WxHxD)	57 x 117 x 33mm	105 x 50 x 32mm
Accessory Socket	2-Pin Kenwood	2-Pin Motorola
Kit Includes	1 x Radio, 1 x Belt Clip, 1 x Desktop Charger & Wall Adaptor, 1 x 1800mAh Battery	1 x Radio, 1 x Belt Clip, 1 x Desktop Charger, 1 x Wall Adaptor, 1 x Rechargeable Battery

Accessories

	BR02	BR02	G15	G15
Code	BA21	BA22	MA27-M	MA25-M
Description	Microphone & Earphone 2 Pin Kenwood	Speaker/Microphone 2 Pin Kenwood	Microphone & Earphone 2 Pin Motorola	Speaker/Microphone 2 Pin Motorola
	BR02	G15	G18	
Code	M-CA-PB-BR02	M-CA-PB-G15	PB-G15	
Description	6 Station Charger	Six Station Charger	Spare LI-ION Battery Pack	

Bluetooth Accessories

Programming Kit

	BR02	G18	BR02, G18	BR02, G18	BR01 / 02	G18
Code	WA-DONGLE-BR02	WA-DONGLE-M	WA21	WA-MIKE-M	PRG-10	PRG-15
Description	Bluetooth Dongle 2 Pin Kenwood	Bluetooth Dongle 2 Pin Motorola	Bluetooth Mic & Earphone Phone Requires B/Tooth Dongle	Bluetooth Speaker/ Microphone Requires Bluetooth Dongle	Software + Cable	

DIY/HOBBY TWO WAY RADIO PMR 446



Hobby / Leisure Radios

Common Features

SCAN, Vox, Keypad lock, Roger Beep, Battery Indicator.
• Display: Backlit LCD

NEW



NEW



- Double PTT
- Baby sitter function
- Dual Watch
- Vibra call

Code	XT30-PRO	G9 PRO	G7E PRO
Channels	16 PMR466	PMR446 16 + 16 Pre-programmed / 1-69 (LPD)	PMR446 1-8 / 1-69 LPD
Tones	38 CTSS tones	38 CTSS / 104 DCS	38 CTCSS / 104 DCS
Operate with Autonomy	300 mAh / 3 x AAA Up to 5hrs	Ni-MH batteries 1800 mAh / 4 X AA Up To 21Hrs	Ni-MH 800mAh / 4 x AA up to 15hrs
Transmission Power	500mW	10 - 500mW Selectable	10 - 500mW (Selectable)
Dimensions (WxHxD)	48 x 90 x 29mm	64 x 126 x 36mm	58 x 122 x 34mm
Kit Includes	2 x Radios with belt clip, 6 x AAA Rechargeable Batteries 300mAh, 1 x 2-Way, USB/Micro USB Cable	1 x Radio, 1 x Desktop Charger, 1 x Wall Adaptor, 1 x Belt Clips, 4 x AA Ni-MH Batteries (1800 mAh)	2 x Radios, 1 x Dual Table Charger & Wall adaptor, 2 x Belt Clips 2 x 800mAh batteries

Accessories

	G7, G9 	G7, G9 	G7, G9 
Code	R72005	MA28-L	AE38
Description	G7, G9 Belt Clip	Microphone with Earphone 2-Pin Midland	Throat Microphone PTT Finger PTT, 2-Pin Midland
	G7, G9 	G7, G9 	G7, G9 
Code	MW904	ALG7	PB-ATL/G7
Description	Wall Charger	Car Charger	Rechargeable Pack

CCTV POWER SUPPLIES 240VAC



24VAC



12VAC



EVP

ACDC Power Supplies is the cost effective way to power multiple cameras. The power supplies provide a 24VAC or adjustable 12VDC output for 4, 9 or 18 fused outputs.

AC Models

Code	No. of Outputs 24VAC	Output Amps	Max. Amps / Channel
24VAC2.5A4P	4	2.5A	1.1
24VAC5A8P	8	5A	1.1
24VAC10A18P	18	10A	1.1

DC Models

Code	No. of Outputs 12VDC	Output Amps	Max. Amps / Channel
12VDC5A4P	4	5A	1.1
12VDC10A9P	9	10A	1.1
12VDC10A18P	18	10A	1.1

DC/AC Models

Code	No. of Outputs	Output Amps	Max. Amps / Channel
EVP-124M6P16Q	8 x 12VDC + 8 x 24VAC	8 (3A)	1.1

NB: "Output Amps" is a maximum total output amperage for entire power supply

- Supply volts: 90~240VAC
- AC or DC output models available
- Individually protected PTC-type 11A fuse outputs
- Status LED indicator
- Main Power Switch with surge protector
- Includes **IP55** Steel enclosure and transformer
- DC models adjustable from 12.6~15.15VDC
- Dimensions: 196W x 254H x 89Dmm

VEHICLE CCTV & DASH CAMCORDER KITS

Two Camera System - 5" Monitor			Two Camera System - 7" Monitor			
	c/w Monitor Bracket & Connecting Cables		c/w Monitor Bracket & Connecting Cables			
Code	TRM-527		TRM-727T			
	Monitor	Cameras	Monitor	Cameras		
Features	• 5" TFT LCD colour monitor • Removable sun visor • Manual or Automatic display switching, Reverse image switching delay 0-30s • Camera trigger priority set in menu • Resolution: 640 x 480 • Mirror or normal image • Size: 152 x 109 x 50mm	• 1/3" Sharp colour CCD • Resolution 420 TV lines • IP68 • 18 IR LED's for 15m night vision • 12VDC • Viewing angle 130° • Shock proof: 10G	• 7" TFT LCD colour monitor • Removable sun visor • Manual or Automatic display switching, Reverse image switching delay 0-30s • Camera trigger priority set in menu • Resolution: 2400 x 480 • Mirror or normal image • Size: 185 x 124 x 48mm	• 1/3" Sharp colour CCD • Resolution 420 TV lines • IP68 • 12 IR LED's for 10m night vision • 11-32VDC • Viewing angle 130° • Shock proof: 10G		
Four Camera System - 7" Monitor			Dash Camcorder			
	c/w Monitor Bracket & Connecting Cables					
Code	TRM-737		DVR-196			
	Monitor	Cameras				
Features	• 7" TFT LCD colour Quad monitor • Single/Split/Quad view selectable • Removable Sun Visor • Manual or Automatic display switching, Reverse image switching delay 0-30s • Size: 185 x 124 x 48mm	• 1/3" sharp colour CCD • Resolution 420 TV lines • 10 IR LED's for 15m night vision • 12VDC • IP66 • Viewing angle: 130° • Shock proof: 10G	• 170° Wide angle lens • 60mm 2.4" screen • GPS module included • Resolution: 1920 x 1080 (1080P) • SD Card (32GB max) • Internal Mic/Speaker • USB & HDMI plugs • 5VDC supply included or USB			
Accessories						
Code	TRC-4103	TRC-8053	TRC-ECC	TRC-EC	TRC-TEC	MICROSD16GB
Features	• Operating voltage: DC12V • Free view angle: 130° • Horizontal resolution: 420TV lines	• Car back camera • Resolution: 420TVL • Free view angle: 130° • Operating voltage 12-32VDC	• Electrical connection cable with backup fuse • Length: 1.5m	• Extension cable (video) • Length: 1.5m	• Trailer extension cable • Length:15m	MICROSD32GB Micro SD Memory Cards with Adaptor (for DVR-196)

NEW

BACK-UP POWER SUPPLY

Power Supply with Charger




3.2A

6.4A

Code	SH-UPS-3.6AMP	SH-UPS-6.4AMP
Input Voltage	110-230VAC	
Output Voltage	13-14VDC (Adj.)	
Output Current	3.6A	6.4A
Size	200 x 180 x 87mm	275 x 225 x 97mm

Note: Battery to be ordered separately

CCTV POWER DISTRIBUTION BOARDS



Central Supply Connection - Power indicator for main board green and terminals

Code	Output	Output Amps	Max. Amps / Channel
PD-9BSQ	9	10A	1.1

Features

- 10A, 240VAC Main fuse. Includes circuit board only
- Camera Fuse Code: **F600-1A**

RACK-MOUNTED CCTV POWER SUPPLIES

AC/DC Slim-line design. Rack mounted CCTV Power Supplies

Code	No. of Outputs	Output Volts	Output Amps	Max. Amps / Channel
24VAC10A16PR	16	24VAC	10A	1.1

DC Model

Code	No. of Outputs	Output Volts	Output Amps	Max. Amps / Channel
12VDC13A16PR	16	12VDC	13A	1.1

Features

- Supply volts: 176~264VAC
- Status LED indicator
- Includes **IP55** enclosure
- Dimensions: 482W x 170H x 44Dmm



VOLTAGE CONVERTER



ST-LA105-TTQ ST-LA115-TPQ

Features

- Converts 12/ 24 VAC/DC to a regulated 5/ 12/ 24 VDC output
- LED indicator with built-in overload protection

Code	Input Voltage	Output Voltage	Current (A)
ST-LA105-TTQ	12 / 24 VAC/DC	5 / 12/24 VDC	0.5A

VOLTAGE BOOSTER




Code	Input Voltage	Output Voltage	Current
ST-HB105-TTQ	7-24VDC	12 or 24VDC (adjustable)	500mA @ 12/ 24VDC

Features

- Compensates DC voltage drops over long cable run
- LED indicator with built-in overload, short-circuit protection

LOW BATTERY CUT-OFF MODULE



Code	I/O Connection	Size
ST-BD01Q	AC input/ output	60 x 45 x 22mm

Features

- Selectable input 12 or 24VDC
- Adjustable cut-off/ restore voltage range
- Dual colour output LED indicator
- Relay contact rating: 7A @ 30VDC


5-IN-1 MULTI-PURPOSE 12VDC TESTER



Code	Test for
ST-BT01Q	1. Voltage 2. Battery load 3. Voltage drop 4. PTC Fuse 5. Polarity test

- LED indicators
- Reverse polarity protection
- Indicates the condition of rechargeable gel 12VDC batteries
- Built-in digital cable with alligator clip for easy connection

ILLUMINATED POWER CONNECTORS



AC/DC Illuminated Power Connectors make trouble-shooting CCTV or other 12VDC or 24VAC equipment easy testing

Code	Description
CA-1510-3FLQ	DC Male Jack with LED and 75mm wire length
CA-1615-06LQ	DC Male Jack to DC Female Plug with LED and 150mm wire length
CA-161T-02SLQ	DC Female Plug to terminal block, snap-in, LED, 63mm wire length

Features

Checks for low voltage AC/DC before connecting to a device.



POWER ADAPTOR



Regulated Power Supply

Code	SNW-0501E
Input	100-240VAC
Output	5VDC / 1A
DC Jack	5.5 x 2.1 x 10mm Straight

For more power supplies, see pg 85



POE Power Adaptor


Code	LYDIZ-24005
Input	90-264VAC
Output	24VDC / 0.5A
Connection	2 x RJ45 (In/Out)

For more power supplies, see pg 85

CAMERA ACCESSORIES




For Single Camera



Code	EVT-PB1	EVT-PBP-VITQ
Description	Transmits a CCTV camera video signal long distances over low cost cable.	6" BNC Digital connection
Features	• Ideal for full-motion colour and black & white cameras • Transmits monochrome video up to 600 metres, or colour up to 400 metres • Low-cost CAT5e/6 unshielded twisted pair (UTP) cable. Works over existing UTP cable • Includes BNC connector and spring clamp terminal block (no need to crimp RJ-45 connectors). Reduces wiring time • High immunity from interference. Built-in impedance coupled device and noise filter	• 6" BNC pigtail connector. • Transmits a monochrome video signal up to 610m. • Passive operation - No external power required. • Built-in impedance coupled device and noise filter

ACTIVE IP BALUN



IPB-A1200Q



IPB-A1100Q

Active IP Baluns are designed to extend any TCP/IP devices beyond the 100m range to 1200m. The unit does not filter out any protocols, codes or applications, so this ensures compatibility with any IP camera and its software.

Code	Description	Input	Output	Voltage
IPB-A1100Q	Active IP Balun over CAT 5e/6	RJ45	RJ45	5VDC
IPB-A1200Q	Active IP Balun over coax (RG59/U)	RJ45	BNC	5VDC

VIDEO AMPLIFIER



Code	EVT-PH16-4T2Q	Features
Transmit Distance	610m	• Connects up to 16 CCTV cameras using low-cost CAT5e/6 UTP cable to a central location • Built-in RS-485 port to P.C. • Mounts in 19" rack • Complete passive operation, no power required
Video Input	16 x 1	
Video Output	16 (BNC)	
Power	500mA	
Compact enclosure	1U (1 3/4")	
Port	Passive	



Code	EVT-AH16-4T2Q	Features
Transmit Distance	2400m	• Works with full motion CCTV cameras up to 2.4km via active video baluns • Mounts in 19" rack • Built-in impedance coupled device and noise filter • Works in conjunction with passive or active video baluns
Video Input	16 x 2	
Video Output	32 (BNC)	
Power	500mA	
Compact enclosure	1U (1 3/4")	
Port	Active	



Code	EVT-AB1Q	Features
Transmit Distance	900m	• Transmitter amplifies the video signal for excellent picture quality at long distances • Inc BNC connector and removable terminal blocks • Gold-plated BNC connector • Surge, ground and transient protection
Video Input	1	
Video Output	1	
Power	300mA	
Compact enclosure	59 x 43 x 41mm	
Port	Active	

VIDEO AMPLIFIER



VA-2101B-WQ



VA-2404B-WQ

Code	VA-2101B-WQ	VA-2404B-WQ
Video Input Channel	1	4
Video Output Channel	1	4
Video Input level	0.8~1.2Vpp, 75 chins	0.8~1.2Vpp, 75 chins
Gain adjustment	+ 60dB @ 5MHz	+ 60dB @ 5MHz
Operating Voltage	12VDC	12VDC
Power consumption	100mA	200mA

Features

- Video Amplifier compensates for video loss
- Transmits up to 1km
- Connects to video camera, multiplexer, VCR, DVR, etc.

VIDEO DISTRIBUTOR



VA-1102B-WQ



VA-1104B-WQ

Code	No. of Video		Video Input Level
	Input	Output	
VA-1102B-WQ	1	2	0.8 ~ 102Vp-p, 75Ω
VA-1104B-WQ	1	4	0.8 ~ 102Vp-p, 75Ω

Features

- Distributes video feed for NTSC or PAL
- Compatible with colour or black & white signals
- LED to indicate power 12VDC or 24VDC
- 1 Video input to 2 or 4 video outputs

BNC TO VGA CONVERTER



Code	Input Signal	Output Signal	Power
VC-IBAQQ	BNC	VGA (DBIS VGA Connector)	5VDC

Features

- Converts almost any LCD Monitor into a security monitor
- Video auto-configure NTSC or PAL Input
- On-screen display function: colour, contrast & brightness

HDMI VIDEO

HDMI Over CAT 5e/6



MVE-AH010Q

VGA Input & Stereo Audio to HDMI Converter



MVA-WH01Q

Code	MVE-AH010Q	MVA-WH01Q
Video Input signal	0.5-1.0Vpp	0.5-1.0Vpp
DDC Input Signal	5Vpp (TTL)	5Vpp
HDMI Output	HDMI 1.3	HDMI 1.2A + HDCP 1.0/1.1
Resolution	480p, 576p, 720p, 1080p	480i, 576i, 1080i, 480p, 576p, 720p, 1080p
Power Adapter	2A@5VDC	1A@5VDC
Link Connection	RJ-45 x 2	Video: VGA, Audio: Dual RCA Stereo
Features	• Works with full-motion • Video and audio signal up to 60m • Connect HDMI equipment using low-cost CAT 5e/ 6 UTP cables	• The MVA-WH01Q VGA and stereo audio to HDMI convertor takes a VGA and stereo audio signal input and outputs as HDMI signal

CAMERA ACCESSORIES



Wireless Transmission Module - 1000 meters

Code	Description
ZT-F1500A	1000 meters Transmitter & Receiver without obstruction

Features

- 1000mW transmission power for long distance surveillance
- Frequency: 900MHz-1.230MHz 4 CH
- Modulation Mode: FM

CAMERA ACCESSORIES

Connectors & Adaptors

					
Code	ZD-805068/5	ZD-805073	ZD-805081	SP2104	ZD-805075/5
Description	Connector BNC Male crimp type for RG58, 59, 6/U	Adaptor BNC Male / RCA Female	Adaptor T BNC Female to 2 x BNC Male	12V Male Plug	Connector BNC Male twist type for RG58, 59, 6/U
					
Code	ZD-805074	ZD-805082	CN031/5	S0239CH	PL259
Description	Adaptor RCA Male / BNC Female	Adaptor T BNC Male to 2 x BNC Female	Female / Female	UHF Female Socket	UHF Male Plug

CCTV Cable - Mill Spec 75 OHM - 100m Roll



Code	Solid Conductor	Size (mm)
E-POWERAX*	RG 59 + POWER	Copper with 0.5mm Twinflex
*Add Length to Code: 1 (1m), 100 (100m Roll), 500 (500m Roll)		Cable: 24 x 0.20mm Copper

CCTV Microphone		CCTV Accessories	
The CCTV Microphone is the ideal way to add sound pick-up to existing camera installations. 			
Code	VM-101Q	CA-161R	MC-1101-09FQ
Features	• Omni-directional pick-up pattern • RCA jack for audible output • 12VDC jack for power	• DC Plug to terminal block for easy connection from terminal to plug	• HDMI cables • Supports HDMI v1.3 for type A • Gold-plated connector

Camera Brackets

Code	Description
J-107	Mounting Bracket
J-109	Mounting Bracket

Camera Brackets

Code	Description	Type
TP-203B	Mounting bracket	Plastic
TP-203I	Mounting bracket	Plastic
TP-206	Mounting bracket	Plastic
TP-205N	Mounting bracket	Metal
TP-207	Mounting bracket	Metal
TP-208	Mounting bracket	Metal

Camera Housings with Heater

Code	Description
ST8009	Outdoor Camera Housing with 20W Heater Blower 230VAC

Outdoor Aluminium Camera Housing

Code	Description	Size (mm)
TP-603	Housing with movable top 8 lock	131 x 106 x 300
TP-6031R	Housing with built-in IR Lens	142 x 115 x 370
TP-208H	Housing with movable top	138 x 117 x 375



ANALOGUE HD CAMERAS

	Short Range Fixed Lens Bullet	Long Range Fixed Lens Bullet		Varifocal Lens Bullet
	IP67  NEW	IP66 	IP67  NEW	IP67  NEW
Code	DS-2CE16DOT-LFS-2.8	DS-2CE16DOT-IT5F	DS-2CE17DOT-IT5F	DS-2CE19DOT-VFIT3F
	HD 1080p Hybrid Turbo Bullet 2.8mm Analogue HD Output 4:1 Feature: TVI/AHD/CVI/CVBS Smart IR, 20m Distance True Day/Night	HD 1080p long range EXIR Hybrid Turbo Bullet Camera Analogue HD Output 4:1 Feature: TVI/AHD/CVI/CVBS IR 80m distance True Day/Night	HD 1080pHybrid Turbo Bullet Camera 3.6mm Analogue HD Output 4:1 Feature: TVI/AHD/CVI/CVBS Smart IR, 80m Distance True Day/Night	HD 1080p Infrared Hybrid Turbo Bullet Camera 2.7-13.5mm Analogue HD Output 4:1 Feature: TVI/AHD/CVI/CVBS Smart IR, 40m Distance True Day/Night
	Fixed Lens Dome			Covert/Pinhole
	IP66 	IP66 		
Code	DS-2CE56D0T-IRMF	DS-2CE56D0T-IRF	DS-2CS54C8T-PH	
Description	HD 1080p Infrared Hybrid Turbo Turret Camera Analogue HD Output 4:1 Feature: TVI/AHD/CVI/CVBS Smart IR, 20m distance True Day/Night	HD 1080p Infrared Hybrid Turbo Turret Camera Analogue HD Output 4:1 Feature: TVI/AHD/CVI/CVBS Smart IR, 20m distance True Day/Night	HD 720p WDR Covert/Turbo Pinhole Camera 1MP progressive scan CMOS Ultra low light 2.8mm fixed lens CVBS switchable analogue	
	Varifocal Lens Dome			
	IP66 	IP67  NEW	IP67  NEW	
Code	DS-2CE56C2T-VFIR3-CVBS	2CE56DOT-VFIR3	DS-2CE79DOT-VFIR3	
Description	HD 720p Varifocal IR Turbo Turret Camera 2.8-12mm OSD & CVBS/720p HD Output Customisation Smart IR, 40m IR distance True Day/Night	HD 1080p InfraredTurbo Turret Camera 2.8-12 mm Analogue HD Output 1 HD Output Over Coaxial Smart IR, 40m Distance True Day/Night	HD 1080p Infrared Hybrid Turbo Bullet Camera 2.7-13.5mm Analogue HD Output Switchable Video Output 4:1: TVI,AHD,CVI,CVBS Smart IR, 40m Distance True Day/Night	

DIGITAL VIDEO RECORDERS

Hard Disks excluded	NEW 		NEW 
Code	DS-7104HQHI-K1	DS-7208HQHI-K1	IDS-7208HQHI-M1/S
Description	4 HD 1080p Channel HDTV/ Turbo DVR IP/HDTV/AHD/HDCVI/CVBS Inputs 1 Channel Audio In/Output HDMI/VGA Output Hard Disk: 1 SATA Interface (6TB Max)	8 Channel 1080p HDTV/ Turbo DVR Self Adaptive HDTV/CVI/AHD/CVBS Signal Input 1 Channel Audio In/Output HDMI/VGA/CVBS Output Hard Disk: 1 SATA interface(6TB max)	8 Channel HD 1080p HDTV/ Turbo DVR IP/HDTV/AHD/HDCVI/CVBS Inputs 1 Channel Audio Input/Output HDMI/VGA/CVBS Output Hard Disk: 1 SATA Interface (10TB Max)
Hard Disks excluded		NEW 	NEW 
Code	DS-7316HQHI-K4	IDS-7216HQHI-M2/S	DS-7332HQHI-K4
Description	16 Channel 1080p HDTV/ Turbo DVR Self Adaptive HDTV/HDCVI/AHD/CVBS Signal Input 1 Channel Audio In/Output. HDMI (4k)/VGA/CVBS Output Hard Disk: 4 SATA int.(8TB max ea.)	16 Channel HD 1080p HDTV/ Turbo DVR IP/HDTV/AHD/HDCVI/CVBS Inputs 1 Channel Audio In/Output. HDMI (4k)/VGA/CVBS Output Hard Disk: 1 SATA Interface (10TB Max)	32 Channel HD 1080p HDTV/ Turbo DVR IP/HDTV/AHD/HDCVI/CVBS Inputs 4 Channel Audio Input/Output HDMI/ VGA/CVBS Output Hard Disk: 4 SATA Interface (10TB Max)

WHILE
STOCKS
LAST

DAY / NIGHT CAMERAS

	Built-in microphone 			
Code	TP-2000MIR-EX	TP-550SS-MIR	TP-550SS-DN	TP-3600XLA
Sensor	1/3" Sony Ex view CCD	1/3" Sony CCD	1/3" Sony CCD	1/4" Sony CCD
Lens	CS/C - Direct drive	CS/C - Direct Drive	CS/C - Direct drive	ICR
Resolution	550TVL	550TVL	550TVL	550TVL
Illumination	0.05lux / f1.0	0.08lux / f1.0	0.08lux / f1.2	0.7lux / f1.6
Voltage/Current	12VDC / 24VAC	12VDC / 24VAC	12VDC / 24VAC	12VDC
Size (mm)	60 x 50 x 110	60 x 50 x 120	60 x 50 x 120	57 x 61 x 110
Focal Iris	Auto	Mechanical IR Cut Filter	Auto	Mechanical IR Cut Filter

WHILE
STOCKS
LAST

IR CAMERAS

										
Code	L752G38-2	L773G38-2	L780G38-2	L751G38-3N	L773G38-3N	L780G38-3N	L751G38-4N	L773G38-4N	L780G38-4N	L751G38
Sensor	1/3" Sony CCD	1/3" Sony CCD	**EFFIO E**	1/3" Sony CCD	1/3" Sony CCD	**EFFIO E**	1/3" Sony CCD	1/3" Sony CCD	**EFFIO E**	1/3" Sony CCD
Lens	3.6mm fixed lens			2.8mm manual zoom			2.8mm manual zoom			3.6mm fixed lens
Resolution	480 TVL	650 TVL	700 TVL	480 TVL	650 TVL	700 TVL	480 TVL	650 TVL	700 TVL	480 TVL
IR LEDS	30 PC IR (25m)			36 PC IR (30m)			36 PC IR (50m) / 24 PC IR (20m)			24 PC IR (20m)
IP Rating	IP66			IP66			IP66			
Voltage	12V DC			12V DC			12VDC			
Size	200 x 82 x 75mm			228 x 97 x 82mm			295 x 120 x 103 / 175 x 69 x 55			175 x 69 x 55
Illumination	0.1 LUX	0.01 LUX	0.001 LUX	0.1 LUX	0.01 LUX	0.001 LUX	0.01 LUX	0.01 LUX	0.001 LUX	0.01 LUX

WHILE
STOCKS
LAST

DOME CAMERAS

										
Code	L751K1	L773K1	L780K1	L752K5	L773K5	L780K5	L773K11	L780K11	L773K18	L780K18
Sensor	1/3" Sony CCD	1/3" Sony CCD	**EFFIO E**	1/3" Sony CCD	1/3" Sony CCD	**EFFIO E**	1/3" Sony CCD	**EFFIO E**	1/3" Sony CCD	**EFFIO E**
Lens	3.6mm fixed lens			3.6mm fixed lens			2.8-12mm manual zoom		2.8-12mm manual zoom	
Resolution	480 TVL	650 TVL	700 TVL	480 TVL	650 TVL	700 TVL	650 TVL	700 TVL	650 TVL	700 TVL
IR LEDS	24 PC IR (20m)			24 PC IR (20m)			36 PC IR (30m)		36 PC IR (30m)	
IP Rating	IP66			Internal			Internal		Internal	
Voltage	12VDC			12VDC			12VDC		12VDC	
Size	94 x 69mm			94 x 69mm			275 x 93mm		275 x 93mm	
Illumination	0.1 LUX	0.01 LUX	0.001 LUX	0.1 LUX	0.01 LUX	0.001 LUX	0.01 LUX	0.01 LUX	0.001 LUX	0.01 LUX

WHILE
STOCKS
LAST

BOX CAMERAS

			
Code	L750S4	L773S4	L780S4
Sensor	1/3" Sony CCD	1/3" Sony CCD	BNC 1/3" Sony CCD EFFIO E
Lens	No Lens	No Lens	No Lens
Resolution	480 TVL	600 TVL	700 TVL
IR LEDS	Low illumination, ATR, DNR	Low illumination, DWDR, DNR	Low illumination, ATR, DNR
IP Rating	Internal	Internal	Internal
Voltage	12VDC	12VDC	12VDC
Size	110 x 45 x 55mm	110 x 45 x 55mm	110 x 45 x 55mm
Illumination	0.1LUX	0.001LUX	0.001LUX

SECURITY

WHILE
STOCKS
LAST

ANALOGUE SECURITY CAMERAS IP66

			
Code	AHD61DIRZ-ICR-A2	AHD318E-ICR-A2	VC-138CN20
Sensor	1/4" 1MP CMOS	1/4" 1MP CMOS	SONY IMX138
Lens	3.6mm / M12	2.8-12MM Vari-focal	3.6mm
Signal	PAL / NTSC	PAL / NTSC	PAL / NTSC
IR Range	20m	40m	20m
Resolution	1280 x 720	1280 x 720	1280 x 720
Video out	1 Channel BNC HD	1 Channel BNC HD	1 Channel BNC HD
Motion Detection	Yes	Yes	-
Power	12VDC	12VDC	12VDC

					
Code	VCDV138SP20	VCDV-1099NT20	VCDP-1099SH20	AN-SD7800M1/S1B	AN-SD7800D5/C2B
Sensor	SONY IMX138	CMOS	CMOS	1/4" Sony CCD	1/4" Super HAD CCD
Lens	3.6mm	2.8-12mm	3.6mm	4.2-42mm (10 x Optical zoom)	4.0-88mm (22 x Optical zoom)
Resolution	720P (1000TVL)	960H (800TVL)	960H (800TVL)	480TVL	480TVL
Voltage	12VDC	12VDC	12VDC	AC19-30V	AC19-30V
Illumination	IR 20m	IR 20m	IR 20m	1.0Lux Colour	0.01Lux B/W, 1.0Lux Colour
Day/Night Mode	ICR Filter	N/A	ICR Filter	ICR Infrared filter	N/A

 WHILE
STOCKS
LAST

EMBEDDED DVR'S

Stand Alone

		
Code	SD-5004V	DVR-8616XH-E1
Description	• 4 Channel D1 Network DVR • Can take 1 x SATA HDD, up to 2 TB	16CH DVR, 400fps, 960H, VGA,HDMI V/O, 8 A/I, 1 A/O, 2 SATA HDD + E SATA

Entry Level CIF DVR

		
Code	DVR-7108XC-C1	DVR-7116XC-C1
Description	8CH DVR, 200fps, CIF, VGA + BNC, + HDMI video out, 1 Audio in, 1 Audio out, RS485A/B, 1 X SATA HDD	16CH DVR, 400fps, CIF, VGA + BNC + HDMI video out, 2 Audio in, 1 Audio out, RS485A/B, 1 X SATA HDD

LCD/DVR & CAMERA COMBO KITS



Code	L1507D4-KIT (4 cameras)	-	D1901D8-KIT (8 cameras)
Code	L1507D4-DVR (DVR + LCD only)	L1701D4-DVR (DVR + LCD only)	-
	• With 4 x CCD cameras and 4 x 18.3m cables • 15" TFT-LCD monitor with built-in DVR • H.264 compression • Triple operation - simultaneous record, playback, network • Clear and smooth network live monitor • Mouse/ USB backup/ PTZ/ Mobile • HDD up to 1TB capacity • Remote view with Mobile phone • Real time remote view via IE browser • Support network protocol: TCP/IP, DHCP, DDNS, PPPoE and email	• 17" TFT-LCD monitor with built-in DVR • H.264 compression • Triplex operation - simultaneous record, playback, network • Clear and smooth network live monitor • Mouse/ USB backup/ PTZ/ Mobile • HDD up to 1TB capacity • Remote view with Mobile phone • Real time remote view via IE browser • Support network protocol: TCP/IP, DHCP, DDNS, PPPoE and email	• With 8 x CCD cameras & 8 x 18.3m cables • 19" TFT-LCD monitor with built-in DVR

DIGITAL VIDEO RECORDERS (DVR)

H.264
compression
Supports
mobile remote
surveillance



Code	BES-8004VT	BES-8008VT
Front Type	Front Key/ 7" TFT Monitor	Front Key/ 7" TFT Monitor
HDD	1TB SATA HDD	1TB SATA HDD
Video Input/ Output	4ch BNC/ 2ch BNC	8ch BNC/ 2ch BNC
Audio Input/ Output	4ch BNC/ 1ch BNC	8ch BNC/1ch BNC
Alarm Input/ Output	4ch / 1 ch	8ch/1ch
Port - USB	2.0	2.0
Image Quality	CIF/HD1/D1 selectable	CIF
Internet	IE/PPPoE/DDNS	IE/PPPoE/DDNS
Mobile Surveillance	Support Symbian s60 v3.0, Mobile Pocket PC operation system	Support Symbian s60 v3.0, Mobile Pocket PC operation system
Power Adaptor	19V/3.42A DC	19V/3.42A DC
Dimensions (mm)	330 x 230 x 60mm	330 x 360 x 60mm

DIGITAL VIDEO RECORDERS (DVR)





Code	D7444HT-KIT
	4 Channel Real time full channel 960H DVR KIT • Supports: 1280*1024. HDMI: 1920*1080 • Supports 4CH 960H real time recording and playback, with PTZ, alarm • VGA port • SATA Interface HDD*2 up to 2TB • 4 pcs 1/4" MT139 CMOS CAMERA, 700TVL, 36pcs IR, LEDS 3.6mm Lens, IR 20m • 500GB Harddrive included

NEW

DIY WIFI NVR KIT

- Support AI humanoid detection
- Motion Detection Support
- Motion detection alarm push to APP
- Automatic cascade Support
- Supports P2P Cloud connection
- Plug & play quick setup





	4 Channel Camera Kit	8 Channel Camera Kit
Code	YH6104L3MI200-W	YH6108L3MI200-W
Description	• 4 x 2MP / 1080P IR IP67 WiFi Bullet Cameras • 1 x WiFi Network Video Recorder • 4 x Power Adaptors for Cameras • Installation Accessories • Hard Disk Drive to be ordered separately	• 8 x 2MP / 1080P IR IP67 WiFi Bullet Cameras • 1 x WiFi Network Video Recorder • 4 x Power Adaptors for Cameras • Installation Accessories • Hard Disk Drive to be ordered separately

NEW

4CH - LCD WIFI NVR

- Simple and fast plug and play setup
- No network cable required
- Saves time and effort with No need to pair
- Max. 100m distance between camera and NVR (line of sight)
- Not expandable
- Note: **HDD to be ordered separately**



4 CH - LCD NVR + 1080P IP Cameras - 10.1 inch LCD NVR with built in monitor to support real time viewing locally

Code	TV-6125-XMW
WiFi NVR	
Description	• Video quality, playback quality - 1080P • Video Input - 1080P • Video/Audio compression - H.265+/G711A • Power Adaptor - 12VDC/2A • LCD size - 10.1 inch • HDD - 2.5inch HDD max capacity - 4TB • Record & playback storage - TF card, • Supports cloud storage (at a fee) • Supports 2-way audio communication • Illumination Distance - 20m

WiFi Camera IP66

Description	• Resolution - HD 1080P • Power Adaptor - 12VDC/1A • 8pcs Infrared lamp configurable • Infrared distance - 20m • Supports 2-way audio communication
-------------	---


SECURITY

NEW

SMART WIRELESS CAMERAS

Features

- Supports Two way audio communication
- Cloud Storage for motion detected events (optional)
- Pan & Tilt cameras support Auto Tracking
- Support Mobile Remote View & Control
- Supports Video recording



Cloud Storage for Videos

Subscribe



WiFi Control



App Control



Remote Switching



Microphone



Speaker



Set Timers & Schedules




Share Control with Others




Motion Detection




Video Playback




App Features



Automation



Control Direction



Cloud Subscription

	Indoor Camera	Indoor Pan & Tilts (P/T)		Outdoor Bullet Camera IP65	
Note: Power Adaptor Included	 Indoor	 Pan & Tilt	 Pan & Tilt	 Outdoor	 Local Control
					
Code	TV-K530-2MP	TV-288ZD-1MP	TV-638ZD-2MP	TV-6024H-2MP	
Sensor	1/2.7" CMOS Colour				
Lens	3.6mm lens	3.6mm lens		4mm lens	
Resolution	1080P	720P	1080P	1080P	
View Angle	90° View Angle	110° View Angle / Pan 355° / Tilt 90°		85° View Angle	
IR LEDs/Distance	9 x IR LED's/ 5m	6 x IR LED's / 10m		4 x IR LED's/ 20m	
Storage	SD-card Slot support max 128GB, Cloud Storage				
Power Supply	USB 5VDC/1A	USB 5VDC/1A		12VDC/1A	
Day/Night	IR-CUT filter auto switch				
Network	802.11b/g/n 2.4G Wifi only			RJ45/ LAN and 2.4G Wifi	

NEW

BATTERY POWERED WIFI CAMERAS

mapesen


Portable Wifi Camera & Solar Panel IP66

Code	Resolution	Battery	Endurance	Storage
MP-BC3	2MP / 1080P	5200mAh	± 150 days	Micro SD up to 128GB

- 6.8W solar panel
- PIR motion detection & push notification in app
- Two way audio



App Control



WiFi Control



Speaker



Microphone

NEW

CAMERA ACCESSORIES



040-958



040-977

Camera Den-IP66

Code	Description
040-958	φ90mm Mounting Bracket/ Junction Box
040-977	φ110mm Mounting Bracket/ Junction Box

- Designated to accomdate most camera brands
- Easy to install

DIY HD ANALOGUE CCTV KITS

Download the free Mapesen app for Android or IOS for remote viewing 	4 Camera Kit 	8 Camera Kit 
	Code RM5104-2B2D 2 x IP66 HD 1080P True Day/Night Bullet Cameras 2 x Indoor HD 1080P True Day/Night Dome Cameras 1 x 5-in-1 4 Channel DVR 4 x 15m all-in-one Cables 1 x Power Splitter 1 x Power Adaptor - 12V/2A Note: HDD to be ordered separately	Code RM5108-4B4D 4 x IP66 HD 1080P True Day/Night Bullet Cameras 4 x Indoor HD 1080P True Day/Night Dome Cameras 1 x 5-in-1 8 Channel DVR 8 x 15m all-in-one Cables 2 x Power Splitter 2 x Power Adaptor - 12V/2A Note: HDD to be ordered separately

DIY WIFI CCTV KITS

Download the free Mapesen app for Android or IOS for remote viewing 	4 Camera Kit 	8 Camera Kit 
	Code TM6104L2JX100-W 4 x 1MP / 720P IP66 WiFi Bullet Cameras 1 x WiFi Network Video Recorder 4 x Power Adaptors for Cameras Installation Accessories Hard Disk Drive to be ordered separately	Code TM6108L2JX100-W 8 x 1MP / 720P IP66 WiFi Bullet Cameras 1 x WiFi Network Video Recorder 4 x Power Adaptors for Cameras Installation Accessories Hard Disk Drive to be ordered separately

WIFI CAMERAS

Download the free Live Vision app for Android or IOS 	IP66 Bullet Cameras		360° Panoramic	IP67 PTZ Cameras	
					
	Code	MP-L2J4I103-WTA	MP-L2J4I205-WTA	VR-T1E4I132-WTA2	MP-B302I205M-WTA2
	Resolution	1MP / 720P	2MP / 1080P	1.3MP / 960P	2.0MP / 1080P
	Storage	Micro SD up to 64GB	Micro SD up to 64GB	Micro SD up to 64GB	Micro SD up to 64GB
Supply Voltage	12VDC	12VDC	12VDC	12VDC	
Features	• Motion detection alarm function • Two way audio		• Motion detection alarm function • Two way audio • IR Illumination	• 4 x Optical 200m: 2.8-12mm • IR Illumination • Two Way Audio • Motion Detection, Snapshot & Email Alarm Functions	

BATTERY POWERED WIFI CAMERAS

mapesen®

Download the free app for Android or IOS

	Solar WiFi Camera	Covert WiFi Clock Camera	Covert WiFi Plug Camera
	IP66 		
Code	MP-BC1	MP-H2	MP-H3
Resolution	2MP / 1080P	2MP / 1080P	2MP / 1080P
Battery	6600mAh	3000MAh	-
Endurance	± 150 days	±10 Hours	-
Storage	Micro SD up to 32GB	Micro SD up to 64GB	Micro SD up to 128GB
App Name	Macroshare	ELook	ELook
Features	- Built in solar panel - PIR motion detection & push notification in app - Two way audio	- Realtime Audio & Video - Working Digital Clock - IR Night Vision - Motion Detection Funtion	- Realtime Audio & Video - IR Night Vision - Motion Detection Funtion - Powered by Wall Socket

WIRELESS CAMERAS & DVR'S

	Outdoor Cameras		Indoor Camera	Kits	
	IP55 	IP55 			
Code	MWL605*	MWL609	MWL610	MWM014-KIT-1	MWM719-KIT-2
Resolution	1 Megapixel	1 Megapixel	1 Megapixel	Kit Includes:	Kit Includes:
Lens	3.6mm Fixed	3.6mm Fixed	3.6mm Fixed	1 x MWM014 DVR	1 x MWM719 Monitor/DVR
Light	24 x IR LED	24 x IR LED	1 LED Array	2 x MWL609 Camera	2 x MWL605 Camera
Night Vsion	15 - 20m	12 - 15m	12 - 15m	2 x MWL610 Camera	1 x MWL609 Camera
Housing	Metal	Plastic	Plastic		1 x MWL610 Camera
System	720P HD Wireless	720P HD Wireless	720P HD Wireless		

*Add **MS** to code for Microphone + Speaker

	720P HD LCD/DVR	720P Mini DVR	Wireless Colour Camera Kits			
						
Code	MWM719	MWM014	Code	ZT-803CT	ZT-805D	ZT-808A
Range	300m	300m	Transmission Freq.	ISM-2.4GHz	ISM-2.4GHz	1.2GHz
Screen Size	7" (178mm) 16:9	—	Imaging Sensor	1/3" CMOS	1/3" CMOS	1/3" CMOS
No of Channels	4 / (2 x 720P)	4 / (2 x 720P)	Horizontal Res.	380TV Lines	380TV Lines	380TV Lines
Frequency	2.4GHz / P2P network	2.4GHz / P2P network	View Angle	62°	62°	62°
Record Storage	4-128GB SD Card	4-128GB SD Card	Trans. Power	10mW/CE; 2mW/FCC	10mW/CE; 2mW/FCC	1000mW
Max No.Cameras	4	4	Modulation Type	FM	FM	FM
Sensing Modes	Manual, Motion and Scheduled	Manual, Motion and Scheduled	Channel Selectable	—	✓	—
Recording Modes	Push Notification, Pre-Event when motion detected	Push Notification, Pre-Event when motion detected	Audio	✓	✓	✓
			PLL System	✓	✓	✓

Wireless 1CH 2000 Images

Recording on 2G SD Card

Code	D0122MW
------	---------

- Colour CMOS wireless camera
- 20 x IR LED, night vision up to 15m
- Motion detection function
- Record AVI video files or JPG photo images
- A 128MB card (not included) can store over 2000 images or 2500 seconds of AVI videos
- Supports up to 32GB SD card



SEAGATE HARD DRIVES



Seagate SV35 Security Hard Drives

Code	Description
ST1000/1TB	1TB hard drive
ST2000/2TB	2TB hard drive
ST3000/3TB	3TB hard drive
ST4000/4TB	4TB hard drive
ST6000/6TB	6TB hard drive
ST8000/8TB	8TB hard drive

- 24 Hour Running Capacity
- Serial ATA Drive

MONITORS



Code	COMP SCREEN 21.5	COMP SCREEN 23
Description	21.5"	23"


POE SWITCHES

Unmanaged PoE Fast Ethernet Switches

			
Code	POE-1009-8P	POE-2018-16P	POE-2618-16P
Desc.	• 125W • 9 RJ-45 With 8 PoE ports • 10/100M • IEEE802.3af (15.4w)	• 250W • 18 RJ-45 With 16 PoE Ports • 10/100M • IEEE802.3af (15.4w)	• 250W • 18 RJ-45 With 16 PoE Ports • 10/100/1000M • IEEE802.3af (15.4w)

Unmanaged PoE Gigabit Switches

Web Smart Managed PoE Switches

			
Code	POE-2626-24P	POE-2218-16P	POE-2226-24P
Desc.	• 250W • 26 RJ-45 with 24 PoE Ports • 10/100/1000M • IEEE802.3af (15.4w)	• 250W • 16 RJ-45 + 2 1000M Combo With 16 PoE Ports • 10/100M • IEEE802.3af (15.4w)	• 370W • 24 RJ-45 + 2 1000M Combo With 24 PoE Ports • 10/100M • IEEE802.3af (15.4w)

ProSafe & Gigabit Smart PoE Switches



Code	Description
FS728TP	24 port ProSafe 24 Port 10/100 Smart Switch with 4 Gigabit Ports and 24 PoE Ports (195W)
FS728TLP	24 port ProSafe 24 Port 10/100 Smart Switch with 2 dedicated Gigabit Ports and 12 PoE ports (195W)
GS110TP	8 port 10/100/1000 Gigabit Smart managed 8 Port PoE Switch (46W) 2 x SFP slots for fiber
GS728TP	24 port 10/100/1000 Gigabit Smart managed 24 Port PoE Switch (192W) 4 x SFP slots for fiber
GS724TPV2	24 port 1000 Base-T Pro Smart POE managed switch 190W 2 Port 1000 Base-X Fibre SFP

NETWORK (IP) EQUIPMENT IP67

Smart Camera Features: LineCross, Intrusion & Unattended Baggage Detection, Face Detection

	Short Range Bullet Cameras - 15m		Fixed Lens Bullet Cameras		Long Range Bullet Camera - 50m+
Power Supply: 12VDC/POE 120dB WDR					
Code	DS-2CD2025FWD-I		DS-2CD2026-G2-I-4MM	DS-2CD2046G2-I-4MM	DS-2CD2T25FWD-I8
Description	2MP Infrared Network Bullet Camera 4mm fixed lens Up to 30m IR distance		2MP infrared Network Bullet Camera 4mm fixed lens Up to 40m IR distance	4MP infrared Network Bullet Camera 4mm fixed lens Up to 40m IR distance	2MP Ultra Low Light Network Bullet Camera 6mm fixed lens Up to 80m IR distance
	Long Range Bullet Camera		Varifocal Bullet Cameras		
Power Supply: 12VDC/POE 120dB WDR					
Code	DS-2CD2T26G2-ISU/SL		DS-2CD2T46G2-ISU/SL	DS-2CD2655FWD-IZS	DS-2CD4B26FWD-IZS
Description	2MP Ultra Low light Network Bullet Camera 6mm fixed lens Up to 60m IR Distance		4MP Ultra Low light Network Bullet Camera 6mm fixed lens Up to 60m IR Distance	5MP Infrared Varifocal Network Bullet Camera 2.8 - 12mm motorised lens Up to 50m IR distance Audio I/O, Alarm I/O	2MP Dark Fighter Smart Network Bullet Camera 2.8 - 12mm motorised lens Up to 30m IR distance Audio I/O, Alarm I/O
	Varifocal Bullet Cameras				
Power Supply: 12VDC/POE 120dB WDR					
Code	DS-2CD2642FWD-IS	DS-2CD2626G2-IZS	DS-2CD2646G2-IZS	IDS-2CD7A26G0/P-IZHS	IDS-2CD7A46G0/P-IZHS
Description	4MP Infrared Varifocal Network Bullet Camera 2.8 - 12 mm motorised Varifocal lens Up to 30m IR Distance Audio I/O, Alarm I/O	2MP Infrared Varifocal Network Bullet Camera 2.8 - 12 mm motorised Varifocal lens Up to 60m IR Distance Audio I/O, Alarm I/O	4MP Infrared Varifocal Network Bullet Camera 2.8 - 12 mm motorised Varifocal lens Up to 60m IR Distance Audio I/O, Alarm I/O	2MP DeepinView Smart Network Bullet Camera 2.8 - 12 mm motorised Varifocal lens Smart Detection, Observation and Identification Up to 50m IR Distance Audio I/O, Alarm I/O	4MP DeepinView Smart Network Bullet Camera 2.8 - 12 mm motorised Varifocal lens Smart Detection, Observation and Identification Up to 50m IR Distance Audio I/O, Alarm I/O
	Fixed Lens Dome Cameras			Mini Dome Cameras	
Power Supply: 12VDC/POE 120dB WDR					
Code	DS-2CD2126G-I-2.8MM	DS-2CD2146G2H-ISU	DS-2CD2346G2-IU	DS-2CD2525FWD-IS	
Description	2MP Darkfighter Dome Infrared Network Camera 2.8 Fixed Lens Up To 30m IR Range	4MP Infrared Dome Network Camera 2.8 Fixed Lens Up To 30m IR Range	4MP Infrared Turret Network Camera 2.8 Fixed Lens Up To 30m IR Range	2MP Infrared Mini Dome Network Camera 2.8mm fixed lens Up to 10m IR distance Audio I/O, Alarm I/O	
	Varifocal Dome Cameras				
Power Supply: 12VDC/POE 120dB WDR					
Code	DS-2CD2742FWD-IS	DS-2CD2726G2-IZS	DS-2CD2746G2-IZS	IDS-2CD7126G0-IZS	
Description	4MP Infrared Varifocal Network Dome Camera 2.8 - 12 mm motorised Varifocal lens Up To 30m IR Range Audio I/O, Alarm I/O	2MP Infrared Varifocal Network Dome Camera 2.8 - 12 mm motorised Varifocal lens Up to 40m IR Distance Audio I/O, Alarm I/O	4MP Infrared Varifocal Network Dome Camera 2.8 - 12 mm motorised Varifocal lens Up to 40m IR Distance Audio I/O, Alarm I/O	2MP Infrared Varifocal Network Dome Camera 2.8 - 12 mm motorised Varifocal lens Up to 40m IR Distance Audio I/O, Alarm I/O	

SOLAR SECURITY CAMERAS

	IP66 NEW 	IP67 NEW 
Code	DS-2XS2T41G0-ID/4G	DS-2XS2T47G0-LDH/4G
	4MP Solar Powered DIY Security	4MP Solar Powered Professional Camera
	Standalone with built-in Solar Panel & 10Ah Battery	Standalone with built-in Solar Panel & 23Ah Battery
	4mm Fixed Lens	4mm Fixed Lens
	Ethernet 4G GSM Communication	Ethernet 4G GSM Communication
	UP to 30m IR Distance	UP to 30m IR Distance

CAMERA ACCESSORIES

Camera Brackets				
Code	DS-1275ZJ	DS-1602ZJ-COR	DS-1602ZJ-POLE	DS-1662ZJ
Description	Vertical pole mount bracket Stainless Steel clamps Aluminium mounting board	Corner mount bracket For PTZ Dome cameras Hikvision White Aluminium alloy and steel	Vertical pole mount bracket Hikvision White Aluminium alloy and steel	Pendant mount bracket For PTZ Dome cameras Size: 116.5 x 500mm Aluminium alloy and steel

HIKVISION

Network Keyboard Controller

Code	DS-1100KI
Power Supply	12VDC
Consumption	≥ 15W
Size (mm)	435 x 193 x 110
Weight	2Kg
Audio	In: 1 x 3.5mm connector (2V P-P) Out: 1 ch, 3.5mm connector (Linear 560Ω)
Communication	1 x 10/100M network Ethernet 1 x USB 2.0 (Data & software upgrade) 1 x RS232 1 x RS485

Features

- 172mm(7") TFT touch screen display at 800x480 resolution
- 4-axis joystick control
- Live / playback video on screen at up to 1080 resolution
- Compatible with NVR/DVR/DVS, Matrix, Network cameras
- Macro command operation
- Display of decoded video on monitor or video wall
- Shortcut keys for camera setting and pattern control, playback operation, input / output groups, wiper and light control
- 1 channel video for decoding local live view
- Capture and recording to local U-flash disk
- Support for 3 operators (each allowed 1280 devices)
- Support for configuration by WEB server
- Keyboard configuration tool
- Configuration and control of MVC system
- Control up to 255 analogue domes by RS485


HIKVISION

USB Keyboard Controller

Code	DS-1005KI
Power Supply	5VDC
Consumption	≥ 5W
Communication	USB
Size (mm)	167 x 177 x 116

Features

- Power supply and communications by USB port
- 3D PTZ control and 2 joystick buttons
- Up to 15 programmable buttons are available
- Supports digital tube to display the input content
- Supports indicators to show operation status
- Supports various client software platforms for Window switching, PTZ control, Picture capture, Recording Supports USB HID protocol
- Supports USB HID protocol
- Compatible with Windows XP / 7 / 8



